

INDUSTRIAL COMPONENT DATA

3RA2445-8XF32-1AL2 SIEMENS Contactor assembly for star-delta (wye-delta) start AC-3, 75 kW/400 V 230 V AC, 5..

Brand: SIEMENS | Manufacturer Part Number: 3RA2445-8XF32-1AL2



Manufacturer	SIEMENS
MPN / Reference	3RA2445-8XF32-1AL2
Catalog number	24458
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-C9ED288E02
Generated	2026-08-06

Product Overview

Contactor assembly for star-delta (wye-delta) start AC-3, 75 kW/400 V 230 V AC, 50/60 Hz Size S3, screw terminal electrical and mechanical interlock 3 NO+3 NC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Contactor assembly for star-delta (wye-delta) start AC-3, 75 kW/400 V 230 V AC, 50/60 Hz Size S3, screw terminal electrical and mechanical interlock 3 NO+3 NC

product brand name SIRIUS

product designation Contactor assembly for star-delta (wye-delta) start

product type designation 3RA24

manufacturer's article number

? 1 of the supplied contactor 3RT2045-1AL20

? 2 of the supplied contactor 3RT2045-1AL20

? 3 of the supplied contactor 3RT2036-1AL20

? of the supplied RS assembly kit 3RA2943-2C

? of the supplied function module for wye-delta circuits 3RA2816-0EW20

General technical data

size of contactor S3

product extension auxiliary switch No
shock resistance at rectangular impulse
? at AC 6.7 g / 5 ms, 4.0 g / 10 ms
shock resistance with sine pulse
? at AC 10.6 g / 5 ms, 6.3 g / 10 ms
mechanical service life (switching cycles)
? of contactor typical 10 000 000
? of the contactor with added auxiliary switch block typical 10 000 000
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 03/01/2017
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -55 ... +80 °C
Main circuit
number of poles for main current circuit 3
number of NO contacts for main contacts 3
number of NC contacts for main contacts 0
operating voltage at AC-3 rated value maximum 690 V
operational current at AC-3
? at 400 V rated value 150 A
operating power
? at AC-3
- at 400 V rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2445-8XF32-1AL2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.