

INDUSTRIAL COMPONENT DATA

3RA2813-2AW10 SIEMENS Solid-state time-delayed auxiliary switch ON delay Relay 1 changeover contact 24...240..

Brand: SIEMENS | Manufacturer Part Number: 3RA2813-2AW10



Manufacturer	SIEMENS
MPN / Reference	3RA2813-2AW10
Catalog number	28132
Category	Timer block
Minimum order	1 Pcs
Document ID	EO-1425BC39FF
Generated	2026-08-03

Product Overview

Solid-state time-delayed auxiliary switch ON delay Relay 1 changeover contact 24...240 V AC/DC Time range 0.05...100 s
Can be snapped on at the front For 3RT2 S00-S3 contactors and 3RH2 S00 contactor relays Spring-type terminal Varistor for attenuation of the contactor coils integrated

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Solid-state time-delayed auxiliary switch ON delay Relay 1 changeover contact 24...240 V AC/DC Time range 0.05...100 s
Can be snapped on at the front For 3RT2 S00-S3 contactors and 3RH2 S00 contactor relays Spring-type terminal Varistor for attenuation of the contactor coils integrated

product brand name SIRIUS

product designation Solid-state time-delay auxiliary switch

product type designation 3RA28

General technical data

size of contactor can be combined company-specific S00, S0, S2, S3

product component semi-conductor output No

product extension required remote control No

product extension optional remote control No

insulation voltage for overvoltage category III according to IEC 60664 with degree of pollution 3 rated value 300 V

test voltage for isolation test 1.5 kV

degree of pollution 3

surge voltage resistance rated value 4 kV

test voltage for surge voltage test 4 800 V

protection class IP of the terminal IP20

shock resistance according to IEC 60068-2-27 15g / 11 ms

vibration resistance according to IEC 60068-2-6 10 ... 59 Hz: 0.35 mm, 60 ... 150 Hz: 2g

mechanical service life (switching cycles) typical 10 000 000

mechanical service life (switching cycles)

? with contactor 3R.2 of frame size S00 10 000 000

? with contactor 3R.2 of frame size S0 10 000 000

? with contactor 3R.2 of frame size S2 10 000 000

? with contactor 3R.2 of frame size S3 10 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2813-2AW10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.