

INDUSTRIAL COMPONENT DATA

3RA2816-0EW20 SIEMENS Function module star-delta (wye-delta) consisting of basic module and 2 coupling modul..

Brand: SIEMENS | Manufacturer Part Number: 3RA2816-0EW20



Manufacturer	SIEMENS
MPN / Reference	3RA2816-0EW20
Catalog number	28160
Category	Timer block
Minimum order	1 Pcs
Document ID	EO-288CBEF083
Generated	2026-07-29

Product Overview

Function module star-delta (wye-delta) consisting of basic module and 2 coupling modules with integrated connecting cable
Time range 0.5...60 s 24...240 V AC/DC For 3RT2 S00-S3 contactors and 3RH2 S00 contactor relays Varistor for attenuation of the contactor coils integrated

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Function module star-delta (wye-delta) consisting of basic module and 2 coupling modules with integrated connecting cable
Time range 0.5...60 s 24...240 V AC/DC For 3RT2 S00-S3 contactors and 3RH2 S00 contactor relays Varistor for attenuation of the contactor coils integrated

product brand name SIRIUS

product designation function module

design of the product comprising basic module and two coupling modules

product type designation 3RA28

General technical data

size of contactor can be combined company-specific S00, S0, S2, S3

product component semi-conductor output No

product extension required remote control No

product extension optional remote control No

insulation voltage for overvoltage category III according to IEC 60664 with degree of pollution 3 rated value 300 V

test voltage for isolation test 1.5 kV

degree of pollution 3

surge voltage resistance rated value 4 kV

test voltage for surge voltage test 4 800 V

protection class IP of the terminal IP20

shock resistance according to IEC 60068-2-27 15g / 11 ms

vibration resistance according to IEC 60068-2-6 10 ... 59 Hz: 0.35 mm, 60 ... 150 Hz: 2g

mechanical service life (switching cycles) typical 10 000 000

mechanical service life (switching cycles)

? with contactor 3R.2 of frame size S00 10 000 000

? with contactor 3R.2 of frame size S0 10 000 000

? with contactor 3R.2 of frame size S2 10 000 000

? with contactor 3R.2 of frame size S3 10 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typica...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA2816-0EW20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.