

INDUSTRIAL COMPONENT DATA

3RA6120-1BB34 SIEMENS SIRIUS Compact load feeder DOL starter 690 V 24 V AC/DC 50...60 Hz 0.32...1.25 A IP20 ..

Brand: SIEMENS | Manufacturer Part Number: 3RA6120-1BB34



Manufacturer	SIEMENS
MPN / Reference	3RA6120-1BB34
Catalog number	61201
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-B91412E023
Generated	2026-08-04

Product Overview

SIRIUS Compact load feeder DOL starter 690 V 24 V AC/DC 50...60 Hz 0.32...1.25 A IP20 Connection main circuit: screw terminal Connection auxiliary circuit: plug-in, without terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > SIRIUS, compact starter
--------------	--

Additional Product Information

ETIM: EC001037 - Motor starter/Motor starter combination

Value Unit

Rated conditional short-circuit current, type 1, 480 Y/277 V (EF009607) - A

Ambient temperature, upper operating limit (EF009603) - °C

Rated operation power at AC-3, 230 V, 3-phase (EF009599) - kW

Degree of protection (NEMA) (EF011959) -

Rated conditional short-circuit current, type 2, 400 V (EF009605) - A

Supporting protocol for INTERBUS-Safety (EF006662) -

Supporting protocol for SERCOS (EF006657) -

Rail mounting possible (EF003972) -

Supporting protocol for other bus systems (EF003062) -

Supporting protocol for SUCONET (EF003060) -

Supporting protocol for CAN (EF003053) -

Number of indicator lights (EF001965) -

Supporting protocol for Modbus (EF003057) -
Rated conditional short-circuit current, type 2, 230 V (EF009606) - A
Supporting protocol for PROFINET IO (EF007525) -
Supporting protocol for PROFIBUS (EF003052) -
Supporting protocol for TCP/IP (EF003050) -
Number of command positions (EF001372) -
Supporting protocol for EtherNet/IP (EF007521) -
Supporting protocol for Data-Highway (EF003058) -
Rated operation current at AC-3, 400 V (EF009602) - A
Rated power, 460 V, 60 Hz, 3-phase (EF009600) - kW
Supporting protocol for DeviceNet Safety (EF007520) -
Rated power, 575 V, 60 Hz, 3-phase (EF009601) - kW
Supporting protocol for LON (EF003017) -
Suitable for emergency stop (EF001433) -
Supporting protocol for ASI (EF003051) -
Supporting protocol for PROFINET CBA (EF007524) -
Supporting protocol for PROFIsafe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA6120-1BB34 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.