

**INDUSTRIAL COMPONENT DATA**

# 3RA6120-1BP32 SIEMENS SIRIUS Compact load feeder DOL starter 690 V 110...240 V AC/DC 50...60 Hz 0.32...1.25 ..

Brand: SIEMENS | Manufacturer Part Number: 3RA6120-1BP32



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | SIEMENS                                 |
| MPN / Reference | 3RA6120-1BP32                           |
| Catalog number  | 61201                                   |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-FCEE3068F5                           |
| Generated       | 2026-08-04                              |

## Product Overview

SIRIUS Compact load feeder DOL starter 690 V 110...240 V AC/DC 50...60 Hz 0.32...1.25 A IP20 Connection main circuit: screw terminal Connection auxiliary circuit: screw terminal

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                            |
|--------------|------------------------------------------------------------|
| Catalog path | SIEMENS > CONTROL AND CONTACTORS > SIRIUS, compact starter |
|--------------|------------------------------------------------------------|

## Additional Product Information

ETIM: EC001037 - Motor starter/Motor starter combination

Value Unit

Supporting protocol for AS-Interface Safety at Work (EF007519) -

Supporting protocol for PROFINET CBA (EF007524) -

External reset possible (EF003426) -

Supporting protocol for Data-Highway (EF003058) -

Supporting protocol for ASI (EF003051) -

Supporting protocol for LON (EF003017) -

Number of indicator lights (EF001965) -

Rated operation current at AC-3, 400 V (EF009602) - A

Rated power, 575 V, 60 Hz, 3-phase (EF009601) - kW

Rated power, 460 V, 60 Hz, 3-phase (EF009600) - kW

Supporting protocol for Foundation Fieldbus (EF007522) -

Supporting protocol for SERCOS (EF006657) -

Supporting protocol for SUCONET (EF003060) -  
Supporting protocol for PROFIsafe (EF007526) -  
Supporting protocol for EtherNet/IP (EF007521) -  
Degree of protection (NEMA) (EF011959) -  
Rated conditional short-circuit current, type 1, 600 Y/347 V (EF009608) - A  
Rated conditional short-circuit current, type 1, 480 Y/277 V (EF009607) - A  
Rated operation power at AC-3, 230 V, 3-phase (EF009599) - kW  
Rail mounting possible (EF003972) -  
Temperature compensated overload protection (EF009604) -  
Supporting protocol for INTERBUS-Safety (EF006662) -  
Supporting protocol for DeviceNet (EF003059) -  
Suitable for emergency stop (EF001433) -  
Ambient temperature, upper operating limit (EF009603) - °C  
Number of command positions (EF001372) -  
Supporting protocol for CAN (EF003053) -  
Supporting protocol for other bus systems (EF003062) -  
Supporting protocol for....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA6120-1BP32 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.