

INDUSTRIAL COMPONENT DATA

3RA6120-1BP33 SIEMENS SIRIUS Compact load feeder DOL starter 690 V 110...240 V AC/DC 50...60 Hz 0.32...1.25 ..

Brand: SIEMENS | Manufacturer Part Number: 3RA6120-1BP33



Manufacturer	SIEMENS
MPN / Reference	3RA6120-1BP33
Catalog number	61201
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-CF9C406F23
Generated	2026-08-06

Product Overview

SIRIUS Compact load feeder DOL starter 690 V 110...240 V AC/DC 50...60 Hz 0.32...1.25 A IP20 Connection main circuit: plug-in, without terminals Connection auxiliary circuit: screw terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > SIRIUS, compact starter

Additional Product Information

ETIM: EC001037 - Motor starter/Motor starter combination

Value Unit

Supporting protocol for EtherNet/IP (EF007521) -

Suitable for emergency stop (EF001433) -

Supporting protocol for PROFI-safe (EF007526) -

Supporting protocol for Modbus (EF003057) -

Rated conditional short-circuit current, type 1, 480 Y/277 V (EF009607) - A

Rated operation current at AC-3, 400 V (EF009602) - A

Rated power, 460 V, 60 Hz, 3-phase (EF009600) - kW

External reset possible (EF003426) -

Supporting protocol for PROFIBUS (EF003052) -

Temperature compensated overload protection (EF009604) -

Supporting protocol for AS-Interface Safety at Work (EF007519) -

Rated conditional short-circuit current, type 1, 600 Y/347 V (EF009608) - A

Number of indicator lights (EF001965) -
Rated conditional short-circuit current, type 2, 230 V (EF009606) - A
Rated conditional short-circuit current, type 2, 400 V (EF009605) - A
Supporting protocol for SafetyBUS p (EF007527) -
Supporting protocol for DeviceNet Safety (EF007520) -
Supporting protocol for INTERBUS-Safety (EF006662) -
Supporting protocol for SERCOS (EF006657) -
Supporting protocol for TCP/IP (EF003050) -
Number of command positions (EF001372) -
Ambient temperature, upper operating limit (EF009603) - °C
Rated power, 575 V, 60 Hz, 3-phase (EF009601) - kW
Supporting protocol for Foundation Fieldbus (EF007522) -
Supporting protocol for other bus systems (EF003062) -
Supporting protocol for LON (EF003017) -
Supporting protocol for INTERBUS (EF003054) -
Supporting pro...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA6120-1BP33 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.