

**INDUSTRIAL COMPONENT DATA**

# 3RA6250-1DB32 SIEMENS SIRIUS Compact load feeder Reversing starter 690 V 24 V AC/DC 50...60 Hz 3...12 A IP20..

Brand: SIEMENS | Manufacturer Part Number: 3RA6250-1DB32



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | SIEMENS                                 |
| MPN / Reference | 3RA6250-1DB32                           |
| Catalog number  | 62501                                   |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-DC67DEE07F                           |
| Generated       | 2026-08-05                              |

## Product Overview

SIRIUS Compact load feeder Reversing starter 690 V 24 V AC/DC 50...60 Hz 3...12 A IP20 Connection main circuit: Screw terminal Connection control circuit: screw terminal

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > SIRIUS, compact starter**

## Additional Product Information

ETIM: EC001037 - Motor starter/Motor starter combination  
Value Unit  
Supporting protocol for DeviceNet Safety (EF007520) -  
Supporting protocol for Foundation Fieldbus (EF007522) -  
Suitable for emergency stop (EF001433) -  
Number of command positions (EF001372) -  
Rated conditional short-circuit current, type 2, 400 V (EF009605) - A  
Rated power, 460 V, 60 Hz, 3-phase (EF009600) - kW  
Supporting protocol for PROFINET CBA (EF007524) -  
Supporting protocol for INTERBUS (EF003054) -  
Rated power, 575 V, 60 Hz, 3-phase (EF009601) - kW  
Supporting protocol for EtherNet/IP (EF007521) -  
Supporting protocol for LON (EF003017) -  
Supporting protocol for AS-Interface Safety at Work (EF007519) -

Degree of protection (NEMA) (EF011959) -  
Supporting protocol for SERCOS (EF006657) -  
Rail mounting possible (EF003972) -  
Supporting protocol for other bus systems (EF003062) -  
Supporting protocol for DeviceNet (EF003059) -  
Supporting protocol for CAN (EF003053) -  
Supporting protocol for ASI (EF003051) -  
Number of indicator lights (EF001965) -  
Rated conditional short-circuit current, type 1, 600 Y/347 V (EF009608) - A  
Rated conditional short-circuit current, type 1, 480 Y/277 V (EF009607) - A  
Rated conditional short-circuit current, type 2, 230 V (EF009606) - A  
Rated operation power at AC-3, 230 V, 3-phase (EF009599) - kW  
Supporting protocol for SafetyBUS p (EF007527) -  
External reset possible (EF003426) -  
Supporting protocol for PROFINET IO (EF007525) -  
Temperature compensated overload protection (EF0096...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA6250-1DB32 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.