


INDUSTRIAL COMPONENT DATA

3RA6920-1A SIEMENS Main circuit terminals (input and output side) Connection main circuit: screw terminal 2 ..

Brand: SIEMENS | Manufacturer Part Number: 3RA6920-1A



Manufacturer	SIEMENS
MPN / Reference	3RA6920-1A
Catalog number	69201
Category	Rail terminal bar
Minimum order	1 Pcs
Document ID	EO-B5CE296C99
Generated	2026-08-05

Product Overview

Main circuit terminals (input and output side) Connection main circuit: screw terminal 2 main circuit terminals per package (1 x input side 1 x output side differ)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > SIRIUS, compact starter

Additional Product Information

ETIM: EC000275 - Rail terminal bar

Value Unit

Number of poles (EF001391) 3

Nominal current (EF000001) - A

Connection type (EF000124) Screwing

Mounting method (EF000003) DIN rail

Number of connections total (EF008299) 0

Number of connections < 6 mm² (EF001155) 0Number of connections 10 mm² (EF001156) 0Number of connections 16 mm² (EF001158) 0Number of connections 25 mm² (EF001157) 0Number of connections > 25 mm² (EF001159) 0

Number of connections < AWG 6 (EF011966) 0

Number of connections AWG 6 (EF011967) 0

Number of connections AWG 4 (EF011968) 0
Number of connections AWG 2 (EF011969) 0
Number of connections AWG 4/0 (EF011970) 0
Number of connections 250 kcmil (EF011971) 0
Number of connections > 250 kcmil (EF011972) 0
Contact safe (EF004521) FALSE
Height (EF000040) 32.0 mm
Width (EF000008) 45.0 mm
Depth (EF000049) 30.0 mm
Main circuit terminals (input and output side) Connection main circuit: screw terminal 2 main circuit terminals per package (1 x input side 1 x output side differ)
General technical data
Product brand name SIRIUS
Product designation main circuit terminals (ingoing as well as outgoing)
Protection class IP IP20
Relative humidity during operation % 10 ... 90
Ambient temperature
? during transport °C -55 ... +80
? during storage °C -55 ... +80
? during operation °C -20 ... +60
Reference code acc. to DIN EN 61346-2 X
Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 X
Installation/ mounting/ dimensions
Width mm 45
Height mm 32...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RA6920-1A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.