

INDUSTRIAL COMPONENT DATA

3RF2330-1BA06 SIEMENS Solid-state contactor 1-phase 3RF2 AC 15 / 15 A / 40 °C 48-600 V / 24 V DC Instantaneo..

Brand: SIEMENS | Manufacturer Part Number: 3RF2330-1BA06



Manufacturer	SIEMENS
MPN / Reference	3RF2330-1BA06
Catalog number	23301
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-48F3DC1325
Generated	2026-08-05

Product Overview

Solid-state contactor 1-phase 3RF2 AC 15 / 15 A / 40 °C 48-600 V / 24 V DC Instantaneous switching
SIRIUS Single phase solid state contactor 3RF2 AC51 30A / AC15 15A 40 Degrees C 400-600V / 24V DC instantaneous maneuver. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Solid-state contactor 1-phase 3RF2 AC 15 / 15 A / 40 °C 48-600 V / 24 V DC Instantaneous switching

product brand name SIRIUS

product designation solid-state contactor

design of the product single-phase

product type designation 3RF23

manufacturer's article number

? _1 of the accessories that can be ordered 3RF2900-3PA88

? _2 of the accessories that can be ordered 3RF2950-0HA16

? _3 of the accessories that can be ordered 3RF2900-0EA18

? _4 of the accessories that can be ordered 3RF2950-0GA16

? _5 of the accessories that can be ordered 3RF2920-0FA08

product designation

- ? _1 of the accessories that can be ordered terminal cover
- ? _2 of the accessories that can be ordered power regulator
- ? _3 of the accessories that can be ordered converter
- ? _4 of the accessories that can be ordered load monitoring
- ? _5 of the accessories that can be ordered load monitoring, basis

General technical data

product function instantaneous switching

power loss [W] for rated value of the current without load current share typical 0.4 W

insulation voltage rated value 600 V

degree of pollution 3

type of voltage of the control supply voltage DC

surge voltage resistance of main circuit rated value 6 kV

shock resistance according to IEC 60068-2-27 15g / 11 ms

vibration resistance according to IEC 60068-2-6 2g

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 05/28/2009

Main circuit

number of poles for main current circuit 1

number of NO contacts for main contacts 1

numbe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RF2330-1BA06 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.