

## INDUSTRIAL COMPONENT DATA

# 3RF2916-0JA13 SIEMENS heating current monitoring current range 16 A / 40 °C 110 ... 230 V 24 V AC/DC remote te..

Brand: SIEMENS | Manufacturer Part Number: 3RF2916-0JA13



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 3RF2916-0JA13                 |
| Catalog number  | 29160                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-E683EBE46A                 |
| Generated       | 2026-08-05                    |

## Product Overview

heating current monitoring current range 16 A / 40 °C 110 ... 230 V 24 V AC/DC remote teach/without control connector for semiconductor relay / contactor

SIRIUS Solid State 3RF2 Function Modules, Load Monitoring, Range 16A 40 Degrees C 110-230V / 24V AC/DC P/ Sirius Relay Semiconductor Contactor.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

SIEMENS &gt; CONTROL AND CONTACTORS &gt; Contactors for switching motors

## Additional Product Information

## Technical data

heating current monitoring current range 16 A / 40 °C 110 ... 230 V 24 V AC/DC remote teach/without control connector for semiconductor relay / contactor

product brand name SIRIUS

product designation heating current monitoring

manufacturer's article number

? \_1 of the accessories that can be ordered 3RF2900-0RA88

product designation

? \_1 of the accessories that can be ordered sealable end cover

## General technical data

product function solid-state relay / solid-state contactor 3RF2

power loss [W] for rated value of the current without load current share typical 1 W

insulation voltage rated value 600 V  
degree of pollution 3  
surge voltage resistance of main circuit rated value 2.5 kV  
shock resistance according to IEC 60068-2-27 15g / 11 ms  
vibration resistance according to IEC 60068-2-6 2g  
design of the switching function NC contact  
reference code according to IEC 81346-2 B  
Substance Prohibitance (Date) 05/01/2012  
Main circuit  
number of poles for main current circuit 0  
number of NO contacts for main contacts 0  
number of NC contacts for main contacts 0  
type of voltage AC/DC  
operating voltage at AC  
? at 50 Hz rated value 110 ... 230 V  
? at 60 Hz rated value 110 ... 230 V  
operating frequency rated value 50 ... 60 Hz  
relative symmetrical tolerance of the operating frequency 10 %  
operating range relative to the operating voltage at AC  
? at 50 Hz 93.5 ... 253 V  
? at 60 Hz 93.5 ... 253 V  
operational current  
? at AC-51 rated value 16 A  
derating temperature 40 °C  
Control cir...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RF2916-0JA13 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.