

INDUSTRIAL COMPONENT DATA

3RF2932-0JA16 SIEMENS heating current monitoring current range 32 A / 40 °C 400 ... 600 V 24 V AC/DC remote te..

Brand: SIEMENS | Manufacturer Part Number: 3RF2932-0JA16



Manufacturer	SIEMENS
MPN / Reference	3RF2932-0JA16
Catalog number	29320
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-6885F64EF2
Generated	2026-08-05

Product Overview

heating current monitoring current range 32 A / 40 °C 400 ... 600 V 24 V AC/DC remote teach/without control connector for semiconductor relay / contactor

SIRIUS Solid State 3RF2 Function Modules, Load Surveillance, range 32A 40 Degrees C 400-600V / 24V AC/DC P/ Sirius Relay Semiconductor Contactor.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

heating current monitoring current range 32 A / 40 °C 400 ... 600 V 24 V AC/DC remote teach/without control connector for semiconductor relay / contactor

product brand name SIRIUS

product designation heating current monitoring

manufacturer's article number

? _1 of the accessories that can be ordered 3RF2900-0RA88

product designation

? _1 of the accessories that can be ordered sealable end cover

General technical data

product function solid-state relay / solid-state contactor 3RF2

power loss [W] for rated value of the current without load current share typical 1 W

insulation voltage rated value 600 V
degree of pollution 3
surge voltage resistance of main circuit rated value 2.5 kV
shock resistance according to IEC 60068-2-27 15g / 11 ms
vibration resistance according to IEC 60068-2-6 2g
design of the switching function NC contact
reference code according to IEC 81346-2 B
Substance Prohibitance (Date) 05/01/2012
Main circuit
number of poles for main current circuit 0
number of NO contacts for main contacts 0
number of NC contacts for main contacts 0
type of voltage AC/DC
operating voltage at AC
? at 50 Hz rated value 400 ... 600 V
? at 60 Hz rated value 400 ... 600 V
operating frequency rated value 50 ... 60 Hz
relative symmetrical tolerance of the operating frequency 10 %
operating range relative to the operating voltage at AC
? at 50 Hz 340 ... 660 V
? at 60 Hz 340 ... 660 V
operational current
? at AC-51 rated value 32 A
derating temperature 40 °C
Control circu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RF2932-0JA16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.