


INDUSTRIAL COMPONENT DATA

3RH1921-1FA04 SIEMENS Attachable block, 4-pole, 4 NC EN 50005 ! Phased-out product! Successor is SIRIUS 3RH2

Brand: SIEMENS | Manufacturer Part Number: 3RH1921-1FA04



Manufacturer	SIEMENS
MPN / Reference	3RH1921-1FA04
Catalog number	19211
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-CA342659CB
Generated	2026-08-02

Product Overview

Attachable block, 4-pole, 4 NC EN 50005 ! Phased-out product! Successor is SIRIUS 3RH2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

Additional Product Information

ETIM: EC000041 - Auxiliary contact block

Value Unit

Number of contacts as change-over contact (EF008257) 0

Number of contacts as normally open contact (EF008256) 0

Number of contacts as normally closed contact (EF008255) 4

Number of fault-signal switches (EF007613) 0

Rated operation current Ie at AC-15, 230 V (EF001385) 6 A

Type of electric connection (EF003961) Screw connection

Model (EF000010) Top mounting

Mounting method (EF000003) Other

Lamp holder (EF000048) None

Attachable block, 4-pole, 4 NC EN 50005 ! Phased-out product! Successor is SIRIUS 3RH2

General technical data

Product brand name SIRIUS

Suitability for use Contactor relay and power contactor

Protection class IP on the front IP20

Ambient temperature

? during storage -55 ... +80 °C

? during operation -25 ... +60 °C

Mechanical service life (switching cycles) typical 10 000 000

Electrical endurance (switching cycles) at AC-15 at 230 V typical 200 000

Contact reliability of auxiliary contacts 1 faulty switching per 100 million (17 V, 1 mA)

Insulation voltage with degree of pollution 3 at AC rated value 690 V

Surge voltage resistance rated value 6 kV

Auxiliary circuit

Number of NC contacts for auxiliary contacts

? instantaneous contact 4

Number of NO contacts for auxiliary contacts

? instantaneous contact 0

Operating current of auxiliary contacts at AC-12

? at 24 V 10 A

? at 230 V 10 A

? maximum 10 A

Operating current

? of auxiliary contacts

- at AC-14

- at 125 V 6 A

- at 250 V 6 A

- at AC-15

- at 24 V 6 A

- at 230....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RH1921-1FA04 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.