INDUSTRIAL COMPONENT DATA

3RH1921-1FA40 SIEMENS Attachable block, 4-pole, 4 NO EN 50005 ! Phased-out product! Successor is SIRIUS 3RH2

Brand: SIEMENS | Manufacturer Part Number: 3RH1921-1FA40



Manufacturer	SIEMENS
MPN / Reference	3RH1921-1FA40
Catalog number	19211
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-7A127320FC
Generated	2026-08-04

Product Overview

Attachable block, 4-pole, 4 NO EN 50005 ! Phased-out product! Successor is SIRIUS 3RH2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

Additional Product Information

ETIM: EC000041 - Auxiliary contact block
Value Unit
Number of contacts as change-over contact (EF008257) 0
Number of contacts as normally open contact (EF008256) 4
Number of contacts as normally closed contact (EF008255) 0
Number of fault-signal switches (EF007613) 0
Rated operation current Ie at AC-15, 230 V (EF001385) 6 A
Type of electric connection (EF003961) Screw connection
Model (EF000010) Top mounting
Mounting method (EF000003) Other
Lamp holder (EF000048) None
Attachable block, 4-pole, 4 NO EN 50005 ! Phased-out product! Successor is SIRIUS 3RH2
General technical data
Product brand name SIRIUS
Suitability for use Contactor relay and power contactor

Protection class IP on the front IP20
Ambient temperature
? during storage -55 ... +80 °C
? during operation -25 ... +60 °C
Mechanical service life (switching cycles) typical 10 000 000
Electrical endurance (switching cycles) at AC-15 at 230 V typical 200 000
Contact reliability of auxiliary contacts 1 faulty switching per 100 million (17 V, 1 mA)
Insulation voltage with degree of pollution 3 at AC rated value 690 V
Surge voltage resistance rated value 6 kV
Auxiliary circuit
Number of NC contacts for auxiliary contacts
? instantaneous contact 0
Number of NO contacts for auxiliary contacts
? instantaneous contact 4
Operating current of auxiliary contacts at AC-12
? at 24 V 10 A
? at 230 V 10 A
? maximum 10 A
Operating current
? of auxiliary contacts
- at AC-14
- at 125 V 6 A
- at 250 V 6 A
- at AC-15
- at 24 V 6 A
- at 230....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RH1921-1FA40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.