

INDUSTRIAL COMPONENT DATA

3RH2122-2AR60 SIEMENS Contactor relay, 2 NO + 2 NC, 400 V AC, 50 Hz, 400 ... 440 V AC 60 Hz, Size S00, Sprin..

Brand: SIEMENS | Manufacturer Part Number: 3RH2122-2AR60



Manufacturer	SIEMENS
MPN / Reference	3RH2122-2AR60
Catalog number	21222
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-E9E6B2C359
Generated	2026-08-06

Product Overview

Contactor relay, 2 NO + 2 NC, 400 V AC, 50 Hz, 400 ... 440 V AC 60 Hz, Size S00, Spring-type terminal CONTACT AUX., 2NA+2NA AC400V 50HZ,AC400 ... 440V 60HZ TAM. S00, SPRING TERMINALS. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactor relays**

Additional Product Information

Technical data

Contactor relay, 2 NO + 2 NC, 400 V AC, 50 Hz, 400 ... 440 V AC 60 Hz, Size S00, Spring-type terminal

product brand name SIRIUS

product designation Auxiliary contactor

product type designation 3RH2

General technical data

size of contactor S00

product extension auxiliary switch Yes

insulation voltage with degree of pollution 3 at AC rated value 690 V

degree of pollution 3

surge voltage resistance rated value 6 kV

shock resistance at rectangular impulse

? at AC 7,3g / 5 ms, 4,7g / 10 ms

shock resistance with sine pulse
? at AC 11,4g / 5 ms, 7,3g / 10 ms
mechanical service life (switching cycles)
? of contactor typical 30 000 000
? of the contactor with added electronically optimized auxiliary switch block typical 5 000 000
? of the contactor with added auxiliary switch block typical 10 000 000
reference code according to IEC 81346-2 K
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -55 ... +80 °C
relative humidity minimum 10 %
relative humidity at 55 °C according to IEC 60068-2-30 maximum 95 %
Main circuit
no-load switching frequency
? at AC 10 000 1/h
? at DC 10 000 1/h
Control circuit/ Control
type of voltage of the control supply voltage AC
control supply voltage at AC
? at 50 Hz rated value 400 V
? at 60 Hz rated value 400 ... 440 V
control supply voltage frequency
? 1 rated value 50 Hz
? 2 rated value 60 Hz
opera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RH2122-2AR60 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.