

INDUSTRIAL COMPONENT DATA

3RH2440-1AF00 SIEMENS Contactor relay, latched, 4 NO, 110 V AC, 50 / 60 Hz, Size S00, screw terminal

Brand: SIEMENS | Manufacturer Part Number: 3RH2440-1AF00



Manufacturer	SIEMENS
MPN / Reference	3RH2440-1AF00
Catalog number	24401
Category	Contacteur relay
Minimum order	1 Pcs
Document ID	EO-87F5BD70D8
Generated	2026-08-05

Product Overview

Contacteur relay, latched, 4 NO, 110 V AC, 50 / 60 Hz, Size S00, screw terminal
SIRIUS Innovations Contacteur hooked, 4NA AC 110V, 50/60HZ, S00 screw connection. Manufactured to order.
Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contacteur relays**

Additional Product Information

Technical data

Contacteur relay, latched, 4 NO, 110 V AC, 50 / 60 Hz, Size S00, screw terminal

product brand name SIRIUS

product designation Auxiliary contacteur

product type designation 3RH2

General technical data

size of contacteur S00

product extension auxiliary switch Yes

insulation voltage with degree of pollution 3 at AC rated value 690 V

degree of pollution 3

surge voltage resistance rated value 6 kV

shock resistance at rectangular impulse

? at AC 7,3g / 5 ms, 4,7g / 10 ms

shock resistance with sine pulse
? at AC 11,4g / 5 ms, 7,3g / 10 ms
mechanical service life (switching cycles)
? of contactor typical 5 000 000
? of the contactor with added electronically optimized auxiliary switch block typical 5 000 000
? of the contactor with added auxiliary switch block typical 5 000 000
reference code according to IEC 81346-2 K
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -55 ... +80 °C
relative humidity minimum 10 %
relative humidity at 55 °C according to IEC 60068-2-30 maximum 95 %
Main circuit
no-load switching frequency
? at AC 10 000 1/h
? at DC 10 000 1/h
Control circuit/ Control
type of voltage of the control supply voltage AC
control supply voltage at AC
? at 50 Hz rated value 110 V
? at 60 Hz rated value 110 V
control supply voltage frequency
? 1 rated value 50 Hz
? 2 rated value 60 Hz
operating range factor control supply....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RH2440-1AF00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.