

INDUSTRIAL COMPONENT DATA

3RH2911-1GA40 SIEMENS Auxiliary switch on the front, 4 NO Current path 1 NO, 1 NO, 1 NO, 1 NO for contactor ..

Brand: SIEMENS | Manufacturer Part Number: 3RH2911-1GA40



Manufacturer	SIEMENS
MPN / Reference	3RH2911-1GA40
Catalog number	29111
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-8D99A68821
Generated	2026-08-05

Product Overview

Auxiliary switch on the front, 4 NO Current path 1 NO, 1 NO, 1 NO, 1 NO for contactor relays Size S00 screw terminal 53/54, 63/64, 73/74, 83/84 for 3RH2140/3RH2440 acc. to EN 50011 Physically coded; only with contactor relays 3RH2140* and 3RH2440* can be combined (according to EN 50011)

SIRIUS Innovations Auxiliary contact, 4NA 1NA, 1NA for auxiliary contacts S00, screw connection DIN EN 50011.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactor relays**

Additional Product Information

Technical data

Auxiliary switch on the front, 4 NO Current path 1 NO, 1 NO, 1 NO, 1 NO for contactor relays Size S00 screw terminal 53/54, 63/64, 73/74, 83/84 for 3RH2140/3RH2440 acc. to EN 50011 Physically coded; only with contactor relays 3RH2140* and 3RH2440* can be combined (according to EN 50011)

General technical data

product brand name SIRIUS

suitability for use Contactor relay

protection class IP on the front IP20

ambient temperature

? during storage -55 ... +80 °C

? during operation -25 ... +60 °C

mechanical service life (switching cycles) typical 10 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 200 000
contact reliability of auxiliary contacts 1 faulty switching per 100 million (17 V, 1 mA)
insulation voltage with degree of pollution 3 at AC rated value 690 V
surge voltage resistance rated value 6 kV
Auxiliary circuit
number of NC contacts for auxiliary contacts
? instantaneous contact 0
? lagging switching 0
number of NO contacts for auxiliary contacts
? instantaneous contact 4
? leading contact 0
operational current of auxiliary contacts at AC-12
? at 24 V 10 A
? at 230 V 10 A
? maximum 10 A
operational current
? of auxiliary contacts
- at AC-14
- at 125 V 6 A
- at 250 V 6 A
- at AC-15
- at 24 V 6 A
- at 230 V 6 A
- at 400 V 3 A
? at AC-15 at 690 V rated value 1 A
operational current
? of auxiliary contacts at DC-12
- at 24 V 10 A
- at 110 V 3 A
- at 220 V 1 A
? with 2 current paths in series at DC-12
- at 24 V rated value 10 A
- at 60...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RH2911-1GA40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.