

INDUSTRIAL COMPONENT DATA

3RH2911-1MA20 SIEMENS Auxiliary switch on the front, 2 NO Current path 1 NO, 1 NO Connection from below for ..

Brand: SIEMENS | Manufacturer Part Number: 3RH2911-1MA20



Manufacturer	SIEMENS
MPN / Reference	3RH2911-1MA20
Catalog number	29111
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-5F6987E3B2
Generated	2026-08-04

Product Overview

Auxiliary switch on the front, 2 NO Current path 1 NO, 1 NO Connection from below for 3RH and 3RT screw terminal 73/74, 83/84

SIRIUS Innovations Auxiliary Contact, 2NA CONEX. FROM BELOW S00 and S0, screw connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactor relays**

Additional Product Information

Technical data

Auxiliary switch on the front, 2 NO Current path 1 NO, 1 NO Connection from below for 3RH and 3RT screw terminal 73/74, 83/84

General technical data

product brand name SIRIUS

suitability for use Contactor relay and power contactor

protection class IP on the front IP20

ambient temperature

? during storage -55 ... +80 °C

? during operation -25 ... +60 °C

mechanical service life (switching cycles) typical 10 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 200 000

contact reliability of auxiliary contacts 1 faulty switching per 100 million (17 V, 1 mA)

insulation voltage with degree of pollution 3 at AC rated value 690 V

surge voltage resistance rated value 6 kV

Auxiliary circuit

number of NC contacts for auxiliary contacts

? instantaneous contact 0

? lagging switching 0

number of NO contacts for auxiliary contacts

? instantaneous contact 2

? leading contact 0

operational current of auxiliary contacts at AC-12

? at 24 V 10 A

? at 230 V 10 A

? maximum 10 A

operational current

? of auxiliary contacts

- at AC-14

- at 125 V 6 A

- at 250 V 6 A

- at AC-15

- at 24 V 6 A

- at 230 V 6 A

- at 400 V 3 A

? at AC-15 at 690 V rated value 1 A

operational current

? of auxiliary contacts at DC-12

- at 24 V 10 A

- at 110 V 3 A

- at 220 V 1 A

? with 2 current paths in series at DC-12

- at 24 V rated value 10 A

- at 60 V rated value 10 A

- at 110 V rated value 4 A

- at 220 V rated value 2 A

- at 440 V rated value 1.3 A

- at 600 V rated value 0.65 A

? with 3....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RH2911-1MA20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.