


INDUSTRIAL COMPONENT DATA

3RH2911-2XA04-0MA0 SIEMENS Auxiliary switch Front-side, 4 NC Current path 1 NC, 1 NC, 1 NC, 1 NC for 3RH2 an..

Brand: SIEMENS | Manufacturer Part Number: 3RH2911-2XA04-0MA0



Manufacturer	SIEMENS
MPN / Reference	3RH2911-2XA04-0MA0
Catalog number	29112
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-47D67DF65C
Generated	2026-08-05

Product Overview

Auxiliary switch Front-side, 4 NC Current path 1 NC, 1 NC, 1 NC, 1 NC for 3RH2 and 3RT2 Spring-type terminal 51/52, 61/62, 71/72, 81/82

AUX CONTACT BLOCK, 4NA, CIRC.: 1NC, 1NC, 1NC, 1NC, P/ AUX CONTACTORS. AND FOR MOTOR, TAM. S00 AND S0, SPRING TERMINALS, 51 / 52.61 / 62.71 / 72.81 / 82 DIN EN 50005.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactor relays**

Additional Product Information

Technical data

Auxiliary switch Front-side, 4 NC Current path 1 NC, 1 NC, 1 NC, 1 NC for 3RH2 and 3RT2 Spring-type terminal 51/52, 61/62, 71/72, 81/82

General technical data

product brand name SIRIUS

suitability for use Contactor relay and power contactor

protection class IP on the front IP20

ambient temperature

? during storage -55 ... +80 °C

? during operation -25 ... +60 °C

mechanical service life (switching cycles) typical 10 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 200 000

contact reliability of auxiliary contacts 1 faulty switching per 100 million (17 V, 1 mA)

insulation voltage with degree of pollution 3 at AC rated value 690 V

surge voltage resistance rated value 6 kV

Auxiliary circuit

number of NC contacts for auxiliary contacts

? instantaneous contact 4

? lagging switching 0

number of NO contacts for auxiliary contacts

? instantaneous contact 0

? leading contact 0

operational current of auxiliary contacts at AC-12

? at 24 V 10 A

? at 230 V 10 A

? maximum 10 A

operational current

? of auxiliary contacts

- at AC-14

- at 125 V 6 A

- at 250 V 6 A

- at AC-15

- at 24 V 6 A

- at 230 V 6 A

- at 400 V 3 A

? at AC-15 at 690 V rated value 1 A

operational current

? of auxiliary contacts at DC-12

- at 24 V 10 A

- at 110 V 3 A

- at 220 V 1 A

? with 2 current paths in series at DC-12

- at 24 V rated value 10 A

- at 60 V rated value 10 A

- at 110 V rated value 4 A

- at 220 V rated value 2 A

- at 440 V rated value 1.3 A

- at 600 V rated value 0.65 A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RH2911-2XA04-0MA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.