

INDUSTRIAL COMPONENT DATA

3RK1107-0BE00-2AA2 SIEMENS AS-i SlimLine Compact module SC22.5, IP20, analog 2AQ-C/V screw terminals 2 x ana..

Brand: SIEMENS | Manufacturer Part Number: 3RK1107-0BE00-2AA2



Manufacturer	SIEMENS
MPN / Reference	3RK1107-0BE00-2AA2
Catalog number	11070
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-59E9D9432E
Generated	2026-08-05

Product Overview

AS-i SlimLine Compact module SC22.5, IP20, analog 2AQ-C/V screw terminals 2 x analog output outputs switchable C/V overall width 22.5 mm

AS-i SlimLine Compact SC22.5 module, IP20, analog., 2AQ-C/V Screw terminals 4 analog outputs Switchable outputs to C/V Width 22.5 mm.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

Additional Product Information

Technical data

AS-i SlimLine Compact module SC22.5, IP20, analog 2AQ-C/V screw terminals 2 x analog output outputs switchable C/V overall width 22.5 mm

product designation Slimline Compact I/O module for use in the control cabinet

design of the product AS-i SC22.5, 2AQ voltage/current

General technical data

protection class IP IP20

design of the slave type standard slave

AS-Interface slave profile S-7.3.5

ID1 code F; Factory setting, changeable

operating voltage according to AS-Interface specification 18 ... 31.6 V

product function suitable for AS-i Power24V Yes

protocol is supported AS-Interface protocol Yes

consumed current from profile conductors of the AS-Interface

? at 30 V maximum 200 mA

? at 24 V with AS-i Power24V maximum 200 mA

type of address setting of AS-i slaves via front addressing socket

display version

? for AS-Interface LED green/red

reference code

? according to EN 61346-2 K

? according to DIN 40719 extended according to IEC 204-2 according to IEC 750 A

shock resistance 15g / 11 ms (modules) or 10g / 11 ms (modules with device connector)

other information An auxiliary external feed (AUX POWER) of between 20 and 30 V DC is necessary for supplying the output circuits. The auxiliary feed must comply with IEC 60990 (PELV), protection class III.

Digital Inputs

number of digital inputs 0

number of digital inputs safety-related 0

Digital Outputs

number of digital outputs 0

type of voltage supply at the outputs AS interface or U_AUX

Analog inputs

number of analog i...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1107-0BE00-2AA2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.