

INDUSTRIAL COMPONENT DATA

3RK1205-0BE00-2AA2 SIEMENS ASIsafe SlimLine Compact module SC17.5F digital safety 2 F-DI, IP20 2 x input for..

Brand: SIEMENS | Manufacturer Part Number: 3RK1205-0BE00-2AA2



Manufacturer	SIEMENS
MPN / Reference	3RK1205-0BE00-2AA2
Catalog number	12050
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-35E8D0C352
Generated	2026-08-05

Product Overview

ASIsafe SlimLine Compact module SC17.5F digital safety 2 F-DI, IP20 2 x input for mechanical sensors Screw terminals Width 17.5 mm

COMP MODULE. ASISAFE SLIMLINE IP20, SEC SLAVE, 2F-DI SCREW TERMINALS, 17.5 MM FOR MECHANICAL SENSORS.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

Additional Product Information

Technical data

ASIsafe SlimLine Compact module SC17.5F digital safety 2 F-DI, IP20 2 x input for mechanical sensors Screw terminals Width 17.5 mm

product designation Slimline Compact I/O module for use in the control cabinet

design of the product AS-i SC17.5F, 2F-DI

General technical data

protection class IP IP20

design of the slave type standard slave

AS-Interface slave profile S-0.B.F

ID1 code F; Factory setting, changeable

operating voltage according to AS-Interface specification 18 ... 31.6 V

product function suitable for AS-i Power24V Yes

protocol is supported AS-Interface protocol Yes
consumed current from profile conductors of the AS-Interface
? at 30 V maximum 50 mA
? at 24 V with AS-i Power24V maximum 50 mA
type of address setting of AS-i slaves via front addressing socket
display version
? as status display of the inputs/outputs Yellow LED
? for AS-Interface LED green/red
reference code
? according to EN 61346-2 K
? according to DIN 40719 extended according to IEC 204-2 according to IEC 750 A
shock resistance 15g / 11 ms (modules) or 10g / 11 ms (modules with device connector)
Digital Inputs
number of digital inputs 0
number of digital inputs safety-related 2
type of input characteristic mechanical contacts
Digital Outputs
number of digital outputs 0
Analog inputs
number of analog inputs 0
Analog outputs
number of analog outputs 0
Safety related data
Safety Integrity Level (SIL) according to IEC 61508 3
performance level (PL) according to EN ISO 13849-1 e
category....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1205-0BE00-2AA2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.