

INDUSTRIAL COMPONENT DATA

3RK1301-0CB20-0AB4 SIEMENS DSS1E-X for ET200S High Feature direct soft starter Setting range 2.4...16 A Elec..

Brand: SIEMENS | Manufacturer Part Number: 3RK1301-0CB20-0AB4



Manufacturer	SIEMENS
MPN / Reference	3RK1301-0CB20-0AB4
Catalog number	13010
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-FB4449EDBD
Generated	2026-08-04

Product Overview

DSS1E-X for ET200S High Feature direct soft starter Setting range 2.4...16 A Electronic switching Electronic protection AC-3, up to 7.5 kW / 400 V expandable for Brake control module 2DI module Motor starter ES Circuit breaker signaling parameterizable DPV 1-capable PROFIENERGY-capable to PN
DSS1E-X FOR ET200S BOOT. DIR. SOFT HIGH FEATURE REGULATION RANGE 2,4...16A ELECTRONIC MANEUVER ELECTRONIC PROTECTION AC-3/UP TO 7,5KW/400V EXPANDABLE FOR MODULE BRAKE CONTROL 2DI MODULE MOTOR STARTER IS SENALIZ. PARAMETERIZABLE AUTOMATIC SWITCH SUITABLE FOR DPV 1 SUITABLE FOR PROFIENERGY IN PN. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

Additional Product Information

Technical data

DSS1E-X for ET200S High Feature direct soft starter Setting range 2.4...16 A Electronic switching Electronic protection AC-3, up to 7.5 kW / 400 V expandable for Brake control module 2DI module Motor starter ES Circuit breaker signaling parameterizable DPV 1-capable PROFIENERGY-capable to PN

product brand name SIMATIC

product designation Motor starters

design of the product direct starter

product type designation ET 200S

General technical data

trip class CLASS 10 and 10A adjustable
product function on-site operation Yes
power loss [W] for rated value of the current without load current share typical 2.4 W
insulation voltage rated value 500 V
degree of pollution 3 at 400 V, 2 at 500 V according to IEC60664 (IEC61131)
surge voltage resistance rated value 6 kV
maximum permissible voltage for safe isolation between main and auxiliary circuit 400 V
shock resistance 5g / 11 ms
vibration resistance 2g
type of assignment 1
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 05/28/2009
product function
? direct start Yes
? reverse starting No
product component motor brake output Yes
product feature
? brake control with 230 V AC No
? brake control with 24 V DC No
? brake control with 180 V DC No
? brake control with 500 V DC No
product extension braking module for brake control Yes
product function short circuit protection Yes
design of short-circuit protection circuit-breakers
breaking capacity maximum short-circuit current (Icu)
? at 400 V rated va...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1301-0CB20-0AB4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.