

**INDUSTRIAL COMPONENT DATA**

# 3RK1301-1EB00-1AA2 SIEMENS RS1-X for ET 200S Standard reversing starter expandable Setting range 2.8...4 A A..

Brand: SIEMENS | Manufacturer Part Number: 3RK1301-1EB00-1AA2



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | SIEMENS                                 |
| MPN / Reference | 3RK1301-1EB00-1AA2                      |
| Catalog number  | 13011                                   |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-8EB47C5C33                           |
| Generated       | 2026-08-04                              |

## Product Overview

RS1-X for ET 200S Standard reversing starter expandable Setting range 2.8...4 A AC-3, 1.5 kW / 400 V Electromechanical starter for brake control module

RS1-X FOR ET 200S ELECTROM INVERTER STARTER. EXPANDABLE ADJUSTMENT RANGE 2,8...4,0A AC-3; 1.5 KW/400V. Manufactured to order. Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

## Additional Product Information

**Technical data**

RS1-X for ET 200S Standard reversing starter expandable Setting range 2.8...4 A AC-3, 1.5 kW / 400 V Electromechanical starter for brake control module

product brand name SIMATIC

product designation Motor starters

design of the product reversing starter

product type designation ET 200S

**General technical data**

trip class CLASS 10

product function on-site operation Yes

power loss [W] for rated value of the current without load current share typical 4.12 W

insulation voltage rated value 500 V

degree of pollution 3 at 400 V, 2 at 500 V according to IEC60664 (IEC61131)  
surge voltage resistance rated value 6 kV  
maximum permissible voltage for safe isolation between main and auxiliary circuit 400 V  
shock resistance 5g / 11 ms  
vibration resistance 2g  
operating frequency maximum 750 1/h  
mechanical service life (switching cycles) of the main contacts typical 100 000  
type of assignment 1  
reference code according to IEC 81346-2 Q  
Substance Prohibitance (Date) 10/26/2016  
product function  
? direct start No  
? reverse starting Yes  
product component motor brake output Yes  
product feature  
? brake control with 230 V AC No  
? brake control with 24 V DC No  
? brake control with 180 V DC No  
? brake control with 500 V DC No  
product extension braking module for brake control Yes  
product function short circuit protection Yes  
design of short-circuit protection circuit-breakers  
breaking capacity maximum short-circuit current (Icu)  
? at 400 V rated value 50 kA  
Electromagnetic compatibility....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1301-1EB00-1AA2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.