

INDUSTRIAL COMPONENT DATA

3RK1308-0AC00-0CP0 SIEMENS Direct-on-line starter High Feature Electronic switching Electronic overload prot..

Brand: SIEMENS | Manufacturer Part Number: 3RK1308-0AC00-0CP0



Manufacturer	SIEMENS
MPN / Reference	3RK1308-0AC00-0CP0
Catalog number	13080
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-B1782F0449
Generated	2026-08-06

Product Overview

Direct-on-line starter High Feature; Electronic switching; Electronic overload protection up to 1.1 kW / 400 V; Adjustment range 0.9 .. 3 A; PROFlenergy; Option: 3DI/LC module

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE
--------------	--

Additional Product Information

Technical data

Direct-on-line starter High Feature; Electronic switching; Electronic overload protection up to 1.1 kW / 400 V; Adjustment range 0.9 .. 3 A; PROFlenergy; Option: 3DI/LC module

product brand name SIMATIC

product category Motor starter

product designation Direct-on-line starter

product type designation ET 200SP

General technical data

trip class CLASS OFF / 5 / 10 adjustable

equipment variant according to IEC 60947-4-2 3

product function Direct-on-line starter

? on-site operation Yes

? intrinsic device protection Yes

? remote firmware update Yes

? for power supply reverse polarity protection Yes
insulation voltage rated value 500 V
degree of pollution 2
overvoltage category III
surge voltage resistance rated value 6 kV
maximum permissible voltage for safe isolation
? between main and auxiliary circuit 500 V
shock resistance 6g / 11 ms
vibration resistance 15 mm to 6 Hz; 2g to 500 Hz
operating frequency maximum 1 1/s
mechanical service life (switching cycles) of the main contacts typical 30 000 000
type of assignment 1
utilization category
? according to IEC 60947-4-2 AC-53a: 3 A: (8-0,7: 70-32)
? according to IEC 60947-4-3 AC-51: 3 A: (1,2-10: 50-360)
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 04/15/2016
product function
? direct start Yes
? reverse starting No
product component motor brake output No
product function short circuit protection Yes
design of short-circuit protection fuse
breaking capacity maximum short-circuit current (I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1308-0AC00-0CP0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.