

INDUSTRIAL COMPONENT DATA

3RK1315-6KS41-0AA0 SIEMENS SIRIUS motor starter M200D AS-i Communication: AS-Interface DOL starter Basic Mec..

Brand: SIEMENS | Manufacturer Part Number: 3RK1315-6KS41-0AA0



Manufacturer	SIEMENS
MPN / Reference	3RK1315-6KS41-0AA0
Catalog number	13156
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-723F6715F8
Generated	2026-08-04

Product Overview

SIRIUS motor starter M200D AS-i Communication: AS-Interface DOL starter Basic Mechanical switching AC-3, 0.75KW / 400 V 0.15 A...2.00 A Electronic overload protection Thermistor: THERMOCLICK / PTC without brake contact 2DI AS-i + 2DI / 1DO on device Han Q4/2 - Han Q8/0

SIRIUS STARTS. MOTOR M200D AS-I COMMUNICATION: AS-INTERFACE DIRECT STARTER BASIC MECHANICAL CLOSURE 3 AC 400V/0.9KW; 0.15A... 2.00A; PROTEC. ELEC. AGAINST OVERLOAD; THERMISTOR: THERMOCLICK / PTC NON-CONTACT BRAKE 2DI AS-I + 2DI / 1ST ON HAN Q4/2-HAN Q8/0 APPARATUS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE
--------------	--

Additional Product Information

Technical data

SIRIUS motor starter M200D AS-i Communication: AS-Interface DOL starter Basic Mechanical switching AC-3, 0.75KW / 400 V 0.15 A...2.00 A Electronic overload protection Thermistor: THERMOCLICK / PTC without brake contact 2DI AS-i + 2DI / 1DO on device Han Q4/2 - Han Q8/0

product brand name SIRIUS

product designation Motor starters

design of the product direct starter

product type designation M200D

trip class CLASS 10

product function

? on-site operation No
? control circuit interface to parallel wiring No
insulation voltage rated value 500 V
degree of pollution 3
surge voltage resistance rated value 6 000 V
maximum permissible voltage for safe isolation
? between main and auxiliary circuit 400 V
? between control and auxiliary circuit 24 V
protection class IP IP65
shock resistance 12g / 11 ms
vibration resistance 7 mm / 2g
mechanical service life (switching cycles) of the main contacts typical 10 000 000
type of assignment 2
certificate of suitability CE
Substance Prohibitance (Date) 07/01/2006
product function
? direct start Yes
? reverse starting No
product component motor brake output No
product feature
? brake control with 230 V AC No
? brake control with 400 V AC No
? brake control with 24 V DC No
? brake control with 180 V DC No
? brake control with 500 V DC No
product extension braking module for brake control No
product function short circuit protection Yes
design of short-circuit protection circuit-breakers
breaking capacity maximum short-circuit curren...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1315-6KS41-0AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.