

INDUSTRIAL COMPONENT DATA

3RK1315-6KS41-1AA0 SIEMENS SIRIUS motor starter M200D AS-i Communication: AS-Interface Reversing starter Bas..

Brand: SIEMENS | Manufacturer Part Number: 3RK1315-6KS41-1AA0



Manufacturer	SIEMENS
MPN / Reference	3RK1315-6KS41-1AA0
Catalog number	13156
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-EC5112A634
Generated	2026-08-05

Product Overview

SIRIUS motor starter M200D AS-i Communication: AS-Interface Reversing starter Basic Mechanical switching AC-3, 0.75KW / 400 V 0.15 A...2.00 A Electronic overload protection Thermistor: THERMOCLICK / PTC without brake contact 2DI AS-i + 2DI / 1DO on device Han Q4/2 - Han Q8/0

SIRIUS ARRANCANC. MOTOR M200D AS-I COMMUNICATION: AS-INTERFACE STARTERS INVERTERS BASIC MECHANICAL CLOSURE 3 AC 400V/0,9KW; 0,15A... 2.00A; PROTEC. ELECT. AGAINST OVERLOAD; THERMISTOR: THERMOCLICK / PTC NON-CONTACT BRAKE 2DI AS-I + 2DI / 1DO ON THE APPARATUS HAN Q4/2-HAN Q8/0. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

Additional Product Information

Technical data

SIRIUS motor starter M200D AS-i Communication: AS-Interface Reversing starter Basic Mechanical switching AC-3, 0.75KW / 400 V 0.15 A...2.00 A Electronic overload protection Thermistor: THERMOCLICK / PTC without brake contact 2DI AS-i + 2DI / 1DO on device Han Q4/2 - Han Q8/0

product brand name SIRIUS

product designation Motor starters

design of the product reversing starter

product type designation M200D

trip class CLASS 10

product function

? on-site operation No

? control circuit interface to parallel wiring No

insulation voltage rated value 500 V

degree of pollution 3

surge voltage resistance rated value 6 000 V

maximum permissible voltage for safe isolation

? between main and auxiliary circuit 400 V

? between control and auxiliary circuit 24 V

protection class IP IP65

shock resistance 12g / 11 ms

vibration resistance 7 mm / 2g

mechanical service life (switching cycles) of the main contacts typical 10 000 000

type of assignment 2

certificate of suitability CE

Substance Prohibitance (Date) 07/01/2006

product function

? direct start No

? reverse starting Yes

product component motor brake output No

product feature

? brake control with 230 V AC No

? brake control with 400 V AC No

? brake control with 24 V DC No

? brake control with 180 V DC No

? brake control with 500 V DC No

product extension braking module for brake control No

product function short circuit protection Yes

design of short-circuit protection circuit-breakers

breaking capacity maximum short-circu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1315-6KS41-1AA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.