

INDUSTRIAL COMPONENT DATA

3RK1395-6KS41-3AD5 SIEMENS SIRIUS motor starter M200D Technology module Reversing starter Mechanical switchi..

Brand: SIEMENS | Manufacturer Part Number: 3RK1395-6KS41-3AD5



Manufacturer	SIEMENS
MPN / Reference	3RK1395-6KS41-3AD5
Catalog number	13956
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-CB2F2418DF
Generated	2026-08-05

Product Overview

SIRIUS motor starter M200D Technology module Reversing starter Mechanical switching AC-3, 0.75KW / 400 V 0.15 A...2.00 A Electronic overload protection Thermistor: THERMOCLICK / PTC with brake contact 180 V DC 4 DI / 2 DO Han Q4/2 - Han Q8/0 with manual on-site operation and key-operated switch via communication module 3RK1305* can be used on PROFIBUS or PROFINET

SIRIUS STARTS. ENGINE M200D MODULE TECHNOLOGIST. ARRANC. MECHANICAL CLOSURE INVERTER 3 AC 400V/0.9KW; 0.15A... 2.00A; PROTEC. ELECT. AGAINST OVERLOAD; THERMISTOR: THERMOCLICK / PTC C / CONTACT. BRAKE 180V DC 4DI/2DO HAN Q4/2-HAN Q8/0 C/ MANUAL AND LOCAL CONTROL AND SECURITY LOCK VIA COMMUNICATION MODULE. 3RK1305* APPLICABLE IN PROFIBUS OR PROFINET. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

Additional Product Information

Technical data

SIRIUS motor starter M200D Technology module Reversing starter Mechanical switching AC-3, 0.75KW / 400 V 0.15 A...2.00 A Electronic overload protection Thermistor: THERMOCLICK / PTC with brake contact 180 V DC 4 DI / 2 DO Han Q4/2 - Han Q8/0 with manual on-site operation and key-operated switch via communication module 3RK1305* can be used on PROFIBUS or PROFINET

product brand name SIRIUS

product designation Motor starters

design of the product reversing starter
product type designation M200D
trip class CLASS 5, 10, 15, 20
product function
? on-site operation Yes
? control circuit interface to parallel wiring No
insulation voltage rated value 500 V
degree of pollution 3
surge voltage resistance rated value 6 000 V
maximum permissible voltage for safe isolation
? between main and auxiliary circuit 400 V
? between control and auxiliary circuit 24 V
protection class IP IP65
shock resistance 12g / 11 ms
vibration resistance 7 mm / 2g
mechanical service life (switching cycles) of the main contacts typical 10 000 000
type of assignment 2
certificate of suitability CE
Substance Prohibitance (Date) 07/01/2006
product function
? direct start No
? reverse starting Yes
product component motor brake output Yes
product feature
? brake control with 230 V AC No
? brake control with 400 V AC No
? brake control with 24 V DC No
? brake control with 180 V DC Yes
? brake control with 500 V DC No
product extension braking module for brake control No
product function short circuit....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1395-6KS41-3AD5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.