

**INDUSTRIAL COMPONENT DATA**

# 3RK1395-6LS71-2AD5 SIEMENS SIRIUS motor starter M200D Technology module DOL starter Electronic switching AC-..

Brand: SIEMENS | Manufacturer Part Number: 3RK1395-6LS71-2AD5



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | SIEMENS                                 |
| MPN / Reference | 3RK1395-6LS71-2AD5                      |
| Catalog number  | 13956                                   |
| Category        | Motor starter/Motor starter combination |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-C14A80C415                           |
| Generated       | 2026-08-03                              |

## Product Overview

SIRIUS motor starter M200D technology module direct-on-line starter electronic switching AC-3, 5.5 kW / 400 V 1.5 A...12.00 A electronic overload protection thermistor: thermoclick / PTC with brake contact 180 V DC 4 DI / 2 DO Han Q4/2 - Han Q8/0 with manual on-site operation and keyswitch via communications module 3RK1305\* can be used on PROFIBUS or PROFINET

SIRIUS ARRANCANC. OF MOTOR M200D MODULE TECHNOLOGY. DIRECT STARTER ELECTRONIC CLOSURE 3 AC 400V/5,5KW; 1,5A... 12.00A; PROTEC. ELECT. AGAINST OVERLOAD; THERMISTOR: THERMOCLICK / PTC C / CONTACT. OF FRENO180V DC 4DI/2DO HAN Q4/2-HAN Q8/0 C/ MANUAL AND LOCAL CONTROL AND SECURITY LOCK VIA COMMUNICATION MODULE. 3RK1305\* APPLICABLE IN PROFIBUS OR PROFINET. Manufactured to order. Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

## Additional Product Information

**Product**

Article Number (Market Facing Number) 3RK1395-6LS71-2AD5

Product Description SIRIUS motor starter M200D technology module direct-on-line starter electronic switching AC-3, 5.5 kW / 400 V 1.5 A...12.00 A electronic overload protection thermistor: thermoclick / PTC with brake contact 180 V DC 4 DI / 2 DO Han Q4/2 - Han Q8/0 with manual on-site operation and keyswitch via communications module 3RK1305\* can be used on PROFIBUS or PROFINET

Product family M200D motor starter modules

Product Lifecycle (PLM) PM400:Announcement of product phase-out

PLM Effective Date Product phase-out since: 01.08.2025

Price data

Region Specific PriceGroup / Headquarter Price Group 42D / 42D

Surcharge for Raw Materials None

Metal Factor LAO-----

Delivery information

Export Control Regulations AL : N / ECCN : 9N9999

Standard lead time ex-works 30 Day/Days

Net Weight (kg) 4,107 Kg

Packaging Dimension 287,00 x 377,00 x 221,00

Package size unit of measure MM

Quantity Unit 1 Piece

Packaging Quantity 1

Additional Product Information

EAN 4011209824331

UPC 662643544831

Commodity Code 85371098

LKZ\_FDB/ CatalogID CC-IC10

Product Group 3722

Group Code R711

Country of origin Germany

Compliance with the substance restrictions according to RoHS directive Since: 01.07.2006

Product class A: Standard product which is a stock item could be returned within the returns guidelines/period.

WEEE (2012/19/EU) Take-Back Obligation Yes

REACH Art. 33 Duty to inform according to the current list of candidates Lead CAS-N...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1395-6LS71-2AD5 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.