

INDUSTRIAL COMPONENT DATA

3RK1903-0CC00 SIEMENS XB2 for ET 200S/DS-X/RS-X brake control module 500 V DC, 0.7 A for motors with mechani..

Brand: SIEMENS | Manufacturer Part Number: 3RK1903-0CC00



Manufacturer	SIEMENS
MPN / Reference	3RK1903-0CC00
Catalog number	19030
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-AB653E4163
Generated	2026-08-06

Product Overview

XB2 for ET 200S/DS-X/RS-X brake control module 500 V DC, 0.7 A for motors with mechanical brakes
XB2 FOR ET 200S DSX/RSX BRAKE CONTROL MODULE; 500V DC 0,7A, P. MOTORS C. MECHANICAL BRAKES.
Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE

Additional Product Information

Technical data

XB2 for ET 200S/DS-X/RS-X brake control module 500 V DC, 0.7 A for motors with mechanical brakes

product brand name SIMATIC

product type designation ET 200S

General technical data

surge voltage resistance rated value 8 kV

shock resistance 5g / 11 ms

vibration resistance 2g

Substance Prohibitance (Date) 05/01/2012

product feature

? brake control with 230 V AC Yes

? brake control with 24 V DC No

? brake control with 180 V DC Yes

? brake control with 500 V DC Yes

type of voltage of the supply voltage for brake control required DC

Electromagnetic compatibility

EMC emitted interference according to IEC 60947-1 CISPR11, ambience A (industrial sector)

EMC immunity according to IEC 60947-1 corresponds to degree of severity 3, ambience A (industrial sector)

conducted interference

? due to conductor-earth surge according to IEC 61000-4-5 2 kV (U > 24 V DC)

? due to conductor-conductor surge according to IEC 61000-4-5 1 kV (U > 24 V DC)

Safety related data

T1 value for proof test interval or service life according to IEC 61508 20 y

protection class IP on the front according to IEC 60529 IP20

touch protection on the front according to IEC 60529 finger-safe

Main circuit

number of poles for main current circuit 2

operating voltage rated value 180 ... 500 V

Inputs/ Outputs

product function

? digital inputs parameterizable No

? digital outputs parameterizable No

number of digital inputs 0

Supply voltage

type of voltage of the supply voltage DC

supply voltage 1 at DC 24 ... 24...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1903-0CC00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.