

INDUSTRIAL COMPONENT DATA

3RK1903-1BB00 SIEMENS PM-D F2 for motor starter power module, Fail-safe up to safety category 4 EN 954-1 for..

Brand: SIEMENS | Manufacturer Part Number: 3RK1903-1BB00



Manufacturer	SIEMENS
MPN / Reference	3RK1903-1BB00
Catalog number	19031
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-F271D2EA0B
Generated	2026-08-06

Product Overview

PM-D F2 for motor starter power module, Fail-safe up to safety category 4 EN 954-1 for auto start protection door can be plugged onto TM-PF30 S47-B0 -B1 30 mm

PM-D F2 FOR ET 200S MOD. POT. SIGUARD P. PROTECTIVE DOOR STARTER, AUTOSTART 2 CHANNELS.

Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE
--------------	--

Additional Product Information

Technical data

PM-D F2 for motor starter power module, Fail-safe up to safety category 4 EN 954-1 for auto start protection door can be plugged onto TM-PF30 S47-B0 -B1 30 mm

product brand name Local Safety Modules

product designation PM-D F2

design of the product for safety circuits

General technical data

product function

? bus communication Yes

? short circuit protection No

mechanical service life (switching cycles) typical 10 000 000

electrical endurance (switching cycles) typical 200 000

Substance Prohibitance (Date) 05/01/2012

Safety related data

safety device type according to IEC 61508-2 Type B

Safety Integrity Level (SIL)

? according to IEC 61508 SIL CL 3

SIL Claim Limit (subsystem) according to EN 62061 3

category according to EN ISO 13849-1 4

Safe failure fraction (SFF) 99 %

average diagnostic coverage level (DCavg) 99 %

PFHD with high demand rate according to EN 62061 0.000000009 1/h

Average probability of failure on demand (PFDavg) with low demand rate acc. to IEC 61508 0.000017 1/y

hardware fault tolerance according to IEC 61508 1

T1 value for proof test interval or service life according to IEC 61508 20 y

safe state Load circuit open

protection class IP on the front according to IEC 60529 IP20

touch protection on the front according to IEC 60529 finger-safe

Control circuit/ Control

type of voltage of the control supply voltage DC

control supply voltage at DC

? rated value 24 V

? rated value 20.4 ... 28.8 V

Installation/ mounting/ dimensions

height 196.5 mm

width...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1903-1BB00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.