

**INDUSTRIAL COMPONENT DATA**

# 3RK1903-1CB00 SIEMENS PM-X for motor starter connection module up to safety category 4 EN 954-1 for feedback..

Brand: SIEMENS | Manufacturer Part Number: 3RK1903-1CB00



|                 |                                                           |
|-----------------|-----------------------------------------------------------|
| Manufacturer    | SIEMENS                                                   |
| MPN / Reference | 3RK1903-1CB00                                             |
| Catalog number  | 19031                                                     |
| Category        | Accessories/spare parts for low-voltage switch technology |
| Minimum order   | 1 Pcs                                                     |
| Document ID     | EO-3D2C31EEE1                                             |
| Generated       | 2026-08-06                                                |

## Product Overview

PM-X for motor starter connection module up to safety category 4 EN 954-1 for feedback circuit and infeed protection 15 mm can be plugged onto TM-X15 S27-01  
CM for ET 200S, SIGUARD connection module up to safety category 4, for power protection

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

## Additional Product Information

**Technical data**

PM-X for motor starter connection module up to safety category 4 EN 954-1 for feedback circuit and infeed protection 15 mm can be plugged onto TM-X15 S27-01

product brand name Local Safety Modules - accessories

product designation PM-X

design of the product for safety circuits

**General technical data**

product function

? bus communication Yes

? short circuit protection No

Substance Prohibitance (Date) 05/01/2012

**Safety related data**

protection class IP on the front according to IEC 60529 IP20

touch protection on the front according to IEC 60529 finger-safe

Control circuit/ Control

type of voltage of the control supply voltage DC

control supply voltage at DC

? rated value 24 V

? rated value 20.4 ... 28.8 V

Installation/ mounting/ dimensions

height 196.5 mm

width 30 mm

Downloads and manuals

depth 117.5 mm

Further information

Siemens has decided to exit the Russian market (see

here). <https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging <https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...) <https://www.siemens.com/ic10>

Industry Mall (Online ordering...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1903-1CB00 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.