

INDUSTRIAL COMPONENT DATA

3RK1908-0AP00-0AP0 SIEMENS Base unit (BU30-MS1) For ET 200SP motor starter With infeed 24 V and 500 V Incl. ..

Brand: SIEMENS | Manufacturer Part Number: 3RK1908-0AP00-0AP0



Manufacturer	SIEMENS
MPN / Reference	3RK1908-0AP00-0AP0
Catalog number	19080
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-56F87DAB88
Generated	2026-08-03

Product Overview

Base unit (BU30-MS1) For ET 200SP motor starter With infeed 24 V and 500 V Incl. infeed bus cover

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

Additional Product Information

Technical data

Base unit (BU30-MS1) For ET 200SP motor starter With infeed 24 V and 500 V Incl. infeed bus cover

product brand name SIMATIC

product category Accessories

product designation BaseUnit

design of the product For AC/DC feed in

product type designation ET 200SP

General technical data

insulation voltage rated value 500 V

degree of pollution 2

surge voltage resistance rated value 6 kV

maximum permissible voltage for safe isolation

? between main and auxiliary circuit 500 V

shock resistance 6g / 11 ms

vibration resistance 15 mm to 6 Hz; 2g to 500 Hz

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 04/15/2016

Safety related data

protection class IP on the front according to IEC 60529 IP20

touch protection on the front according to IEC 60529 finger-safe

Main circuit

number of poles for main current circuit 3

type of voltage of the operating voltage AC

operating voltage rated value 500 V

operating voltage of AC supply 500 V

operational current at AC at 400 V rated value 32 A; Derating, see Manual

Inputs/ Outputs

number of digital inputs 0

Supply voltage

type of voltage of the supply voltage DC

supply voltage 1 at DC rated value 24 V

? minimum permissible 20.4 V

? maximum permissible 28.8 V

supply voltage of DC supply 24 V

ampacity maximum 7 A

Installation/ mounting/ dimensions

mounting position vertical, horizontal

fastening method standard rail

height 215 mm

width 30 mm

depth 75 mm

required spacing with side-by-side mounting

? upwards 50 mm

? down...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1908-0AP00-0AP0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.