

INDUSTRIAL COMPONENT DATA

3RK1908-0AP00-0DP0 SIEMENS Base unit (BU30-MS4) For ET 200SP motor starter Without infeed

Brand: SIEMENS | Manufacturer Part Number: 3RK1908-0AP00-0DP0



Manufacturer	SIEMENS
MPN / Reference	3RK1908-0AP00-0DP0
Catalog number	19080
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-810ED9FD3D
Generated	2026-08-03

Product Overview

Base unit (BU30-MS4) For ET 200SP motor starter Without infeed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

Additional Product Information

Technical data

Base unit (BU30-MS4) For ET 200SP motor starter Without infeed

product brand name SIMATIC

product category Accessories

product designation BaseUnit

design of the product Without feed in

product type designation ET 200SP

General technical data

insulation voltage rated value 500 V

degree of pollution 2

surge voltage resistance rated value 6 kV

maximum permissible voltage for safe isolation

? between main and auxiliary circuit 500 V

shock resistance 6g / 11 ms

vibration resistance 15 mm to 6 Hz; 2g to 500 Hz

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 04/15/2016

Safety related data

protection class IP on the front according to IEC 60529 IP20

touch protection on the front according to IEC 60529 finger-safe

Main circuit

number of poles for main current circuit 3

type of voltage of the operating voltage AC

operating voltage rated value 500 V

operational current at AC at 400 V rated value 32 A; Derating, see Manual

Inputs/ Outputs

number of digital inputs 0

Supply voltage

type of voltage of the supply voltage DC

supply voltage 1 at DC rated value 24 V

? minimum permissible 20.4 V

? maximum permissible 28.8 V

ampacity maximum 7 A

Installation/ mounting/ dimensions

mounting position vertical, horizontal

fastening method standard rail

height 215 mm

width 30 mm

depth 75 mm

required spacing with side-by-side mounting

? upwards 50 mm

? downwards 50 mm

Ambient conditions

installation altitude at height above sea level maximum 4 000 m; For deratin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK1908-0AP00-0DP0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.