

INDUSTRIAL COMPONENT DATA

3RK2100-1CT30-0AA3 SIEMENS AS-i compact module K20 digital A/B slave, 4 DQ, IP67 4 x output, 1 A 24 V DC max..

Brand: SIEMENS | Manufacturer Part Number: 3RK2100-1CT30-0AA3



Manufacturer	SIEMENS
MPN / Reference	3RK2100-1CT30-0AA3
Catalog number	21001
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-189B00CAB2
Generated	2026-08-05

Product Overview

AS-i compact module K20 digital A/B slave, 4 DQ, IP67 4 x output, 1 A 24 V DC max. 1 A for all outputs 4 x M8 socket

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE**

Additional Product Information

Technical data

AS-i compact module K20 digital A/B slave, 4 DQ, IP67 4 x output, 1 A 24 V DC max. 1 A for all outputs 4 x M8 socket

General technical data

design of the product digital I/O modules for operation in the field, IP67 - K20

Type 4 outputs

design of the slave type A/B slave (Spec. 3.0)

I/O configuration 7

ID/ID2 code A/7

Number I/O sockets 4

type of electrical connection of the inputs and outputs M8 screw-type terminals

AS interface total current input max 45 mA

operating voltage according to AS-Interface specification 26.5 ... 31.6 V

Ground terminal not available

Addressing using M12 female connector

AS interface Connection Polarity reversal protection built-in

Note 1 An external additional supply (AUX POWER) of 20 to 30 V DC is required for the supply of the output circuits. The additional supply must comply with VDE 0106 (PELV), protection class III.

Note 2 This module requires a master according to AS-i specifications 3.0

Inputs

number of digital inputs 0

Input circuit PNP transistor

Outputs

number of digital outputs 4

type of voltage of output voltages DC

Outputs external power supply 24 V DC shared round cable connection with AS-Interface connection through M12 female connector

ampacity of the semiconductor output at DC-13 at 24 V 1 A

Outputs aggregate current

? max 2 A

? at $T_u=40\text{ }^{\circ}\text{C}$ max 2 A

type of switching output PNP transistor

design of the pin assignment of the outputs standard assignement

Outputs socket assignment 3 = "-", 4 = output

property of the ou...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK2100-1CT30-0AA3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.