

INDUSTRIAL COMPONENT DATA

3RK2400-1HQ00-0AA3 SIEMENS AS-i compact module K60 digital A/B slave, 8 DI/2 DQ, IP67 3 x 2 inputs and 2 x 1..

Brand: SIEMENS | Manufacturer Part Number: 3RK2400-1HQ00-0AA3



Manufacturer	SIEMENS
MPN / Reference	3RK2400-1HQ00-0AA3
Catalog number	24001
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-AAFDABDD9C
Generated	2026-08-05

Product Overview

AS-i compact module K60 digital A/B slave, 8 DI/2 DQ, IP67 3 x 2 inputs and 2 x 1 input / 1 output max. 200 mA sensor supply Outputs 2 A, 24 V DC 8 x M12 sockets with Y assignment Mounting plate 3RK1901-0CA00 must be ordered separately

COMP. AS-INTERFACE K60 MODULE, ESCL A/B, DIGITAL, 8E/2A, IP67, 3 X 2 E / 2 X 1E/1A, DC 24V 8 X FEMALE M12 SPECIAL FOR SENSOR/ACTUATOR DIAGNOSTICABLE MOUNTING PLATE 3RK1901-0CA00 OR 3RK1901-0CB00 MUST BE ORDERED SEPARATELY.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE
--------------	--

Additional Product Information

Technical data

AS-i compact module K60 digital A/B slave, 8 DI/2 DQ, IP67 3 x 2 inputs and 2 x 1 input / 1 output max. 200 mA sensor supply Outputs 2 A, 24 V DC 8 x M12 sockets with Y assignment Mounting plate 3RK1901-0CA00 must be ordered separately

General technical data

design of the product digital I/O modules for operation in the field, IP67 - K60

Type 8 inputs / 2 outputs

design of the slave type A/B slave

I/O configuration 0 (addr.1) / 7 (addr.2)

ID/ID2 code I/O (addr.1 and 2)

Number I/O sockets 8

type of electrical connection of the inputs and outputs M12 screw-type terminals

AS interface total current input max 300 mA

operating voltage according to AS-Interface specification 26.5 ... 31.6 V

Ground terminal PIN5 of each M12 socket is connected to the grounding wrist strap in the mounting plate using a pin

Addressing front addressing socket

Delivery note the modules are delivered without mounting plate

note module requires two addresses

Note 2 An external additional supply (AUX POWER) of 20 to 30 V DC is required for the supply of the output circuits. The additional supply must comply with VDE 0106 (PELV), protection class III.

Sensor supply

type of voltage supply for power supply using AS-Interface

input voltage 20 ... 30 V

property of the sensor supply short-circuit and overload resistant Yes

ampacity of the sensor supply for all inputs

? at ambient temperature 40 °C 200 mA

Inputs

number of digital inputs 8

type of connection technology 2- and 3-wire technology

Inpu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK2400-1HQ00-0AA3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.