

INDUSTRIAL COMPONENT DATA

3RK3511-1BA10 SIEMENS SIRIUS, interface module DP interface, for modular safety system 3RK3 PROFIBUS DP inte..

Brand: SIEMENS | Manufacturer Part Number: 3RK3511-1BA10



Manufacturer	SIEMENS
MPN / Reference	3RK3511-1BA10
Catalog number	35111
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-8345B7F98A
Generated	2026-08-02

Product Overview

SIRIUS, interface module DP interface, for modular safety system 3RK3 PROFIBUS DP interface 12 Mbps, RS 485 45 mm overall width screw terminal can be parameterized via Safety ES without connection cable
SIRIUS Safety relays, dp-interface interface module, for modular safety system.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Programmable safety relays MSS

Additional Product Information

Technical data

SIRIUS, interface module DP interface, for modular safety system 3RK3 PROFIBUS DP interface 12 Mbps, RS 485 45 mm overall width screw terminal can be parameterized via Safety ES without connection cable

product brand name SIRIUS

product category Modular safety system

product designation Interface module

design of the product DP-Interface

General technical data

protection class IP IP20

shock resistance 15g / 11 ms

degree of pollution 2

certificate of suitability UL approval Yes

vibration resistance according to IEC 60068-2-6 5 ... 500 Hz: 0.75 mm

reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750 K

reference code according to EN 61346-2 K

Communication/ Protocol

protocol is supported

? PROFIBUS DP protocol Yes

Control circuit/ Control

type of voltage DC

inrush current peak at 24 V A 70

duration of inrush current peak at 24 V ms 1

Installation/ mounting/ dimensions

fastening method standard rail

mounting position vertical

width mm 45

height mm 111

depth mm 124

Connections/ Terminals

type of electrical connection screw-type terminals

connectable conductor cross-section for auxiliary contacts

? solid or stranded mm² 0.5 ... 4

? finely stranded

- with core end processing mm² 0.5 ... 2.5

type of connectable conductor cross-sections for auxiliary contacts

? solid 1x (0.5 ... 4 mm²), 2x (0.5 ... 2.5 mm²)

? finely stranded

- with core end processing 1x (0.5 ... 2.5 mm²), 2x (0.5 ... 1.5 mm²)

AWG number as coded connectable conduc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK3511-1BA10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.