


INDUSTRIAL COMPONENT DATA

3RK3511-2BA10 SIEMENS SIRIUS, interface module DP interface, for modular safety system 3RK3 PROFIBUS DP inte..

Brand: SIEMENS | Manufacturer Part Number: 3RK3511-2BA10



Manufacturer	SIEMENS
MPN / Reference	3RK3511-2BA10
Catalog number	35112
Category	Device for monitoring of safety-related circuits
Minimum order	1 Pcs
Document ID	EO-3ED7B4B8E1
Generated	2026-07-31

Product Overview

SIRIUS, interface module DP interface, for modular safety system 3RK3 PROFIBUS DP interface 12 Mbps, RS 485 45 mm overall width spring-type terminal can be parameterized via Safety ES without connection cable
SIRIUS Safety relays, dp-interface interface module, for modular safety system.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Programmable safety relays MSS
--------------	---

Additional Product Information

Technical data

SIRIUS, interface module DP interface, for modular safety system 3RK3 PROFIBUS DP interface 12 Mbps, RS 485 45 mm overall width spring-type terminal can be parameterized via Safety ES without connection cable

product brand name SIRIUS

product category Modular safety system

product designation Interface module

design of the product DP-Interface

General technical data

protection class IP IP20

shock resistance 15g / 11 ms

degree of pollution 2

certificate of suitability UL approval Yes

vibration resistance according to IEC 60068-2-6 5 ... 500 Hz: 0.75 mm

reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750 K

reference code according to EN 61346-2 K

Communication/ Protocol

protocol is supported

? PROFIBUS DP protocol Yes

Control circuit/ Control

type of voltage DC

inrush current peak at 24 V A 70

duration of inrush current peak at 24 V ms 1

Installation/ mounting/ dimensions

fastening method standard rail

mounting position vertical

width mm 45

height mm 113

depth mm 124

Connections/ Terminals

type of electrical connection spring-loaded terminals

connectable conductor cross-section for auxiliary contacts

? solid or stranded mm² 0.25 ... 1.5

? finely stranded

- with core end processing mm² 0.25 ... 1.5

- without core end processing mm² 0.25 ... 1.5

type of connectable conductor cross-sections for auxiliary contacts

? solid 2x (0.25 ... 1.5 mm²)

? finely stranded

- with core end processing 2x (0.25 ... 1.5 mm²)

- without core end...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK3511-2BA10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.