

INDUSTRIAL COMPONENT DATA

3RK3922-1AC10 SIEMENS Starter package for modular Safety system 3RK3 Content: Central unit MSS Advanced conn..

Brand: SIEMENS | Manufacturer Part Number: 3RK3922-1AC10

	Manufacturer	SIEMENS
	MPN / Reference	3RK3922-1AC10
	Catalog number	39221
	Category	Device for monitoring of safety-related circuits
	Minimum order	1 Pcs
	Document ID	EO-4338DE6BE9
	Generated	2026-08-03

Product Overview

Starter package for modular Safety system 3RK3 Content: Central unit MSS Advanced connection: Screw terminal
Software Safety ES V1.0 Premium, USB PC cable

P.MODULAR STARTER PACKAGE SAFETY SYSTEM 3RK3 CONTAINS: MSS ADVANCED CENTRAL MODULE,
MODULAR SAFETY SYSTEM SOFTWARE ES 2008, PC CABLE. Manufactured to order. Non-Cancelable
Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Programmable safety relays MSS
--------------	---

Additional Product Information

Technical data

Starter package for modular Safety system 3RK3 Content: Central unit MSS Advanced connection: Screw terminal
Software Safety ES V1.0 Premium, USB PC cable

product brand name SIRIUS

product category Modular Safety System

product designation Starter kit

suitability for use for monitoring of optoelectronic protective devices according to IEC 61496-1 Yes

suitability for use

? monitoring of floating sensors Yes

? monitoring of non-floating sensors Yes

? position switch monitoring Yes

? EMERGENCY-OFF circuit monitoring Yes
? valve monitoring Yes
? opto-electronic protection device monitoring Yes
? proximity switch monitoring Yes
? safety-related circuits Yes
General technical data
product function
? EMERGENCY STOP function Yes
? protective door monitoring Yes
? protective door monitoring with tumbler Yes
? muting, 2 sensor-parallel Yes
? muting, 4 sensor-parallel Yes
? muting, 4 sensor-sequential Yes
? monitoring parameterizable Yes
? evaluation: electro-sensitive protective equipment Yes
? evaluation: selector switch Yes
? pressure-sensitive mat monitoring Yes
? evaluation: two-hand operator panel Yes
? evaluation: enabling switch Yes
? monitored start-up Yes
? two-hand control according to EN 574 Yes
number of function blocks typical 300
insulation voltage rated value 300 V
degree of pollution 3
surge voltage resistance rated value 2 500 V
consumed current for rated value of supply voltage 1.685 A
protection class IP IP20
? of the enclosure IP20
? of the terminal....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK3922-1AC10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.