

INDUSTRIAL COMPONENT DATA

3RK7243-2AA30-0XB0 SIEMENS SIMATIC S7-1200, CM 1243-2 communication module AS-Interface master according to ..

Brand: SIEMENS | Manufacturer Part Number: 3RK7243-2AA30-0XB0



Manufacturer	SIEMENS
MPN / Reference	3RK7243-2AA30-0XB0
Catalog number	72432
Category	PLC communication module
Minimum order	1 Pcs
Document ID	EO-71FE729C30
Generated	2026-08-05

Product Overview

SIMATIC S7-1200, CM 1243-2 communication module AS-Interface master according to AS-i specification V3.0
SIMATIC S7-1200, CM 1243-2, AS-interface master module for S7-1200, spec. V3.0.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > AS-Interface switchgear, SIMOCODE

Additional Product Information

Technical data

SIMATIC S7-1200, CM 1243-2 communication module AS-Interface master according to AS-i specification V3.0

General technical data

product designation AS-Interface Master

product type designation CM 1243-2

protection class IP IP20

type of electrical connection of the AS-Interface Screw-type connection

type of voltage supply via backplane bus

operating condition separate power supply 24 V No

consumed current

? from profile conductors of the AS-Interface

- at 30 V maximum mA 100

? from backplane bus maximum mA 250

power loss [W] W 2.9

insulation voltage rated value V 500
product function suitable for AS-i Power24V Yes
? note All product versions
product feature redundancy capability No
product function
? web-based management No
? diagnostics via email No
? galvanic isolation Yes
display version
? as status display by LED AS-i, PF, CM, CER, DIAG
type of configuration of the AS-Interface With STEP 7, command interface
Communication/ Protocol
version of the AS-Interface specification V 3.0
AS-Interface master profile is supported M4 (in acc. with AS-interface specification V 3.0)
type of data transmission S7-1200 backplane bus
number of units per CPU maximum 3
number of units per CPU maximum note Max. 3 communication modules in total (CM /CP)
number of interfaces
? as AS-Interface 1
? according to RS 485 0
? according to Industrial Ethernet 0
? according to PROFINET 0
? according to wireless 0
? according to USB 0
? other 0
product component optical interface No
proto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RK7243-2AA30-0XB0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.