

INDUSTRIAL COMPONENT DATA

3RQ2000-2CW01 SIEMENS Coupling relay in industrial enclosure 3 hard gold-plated changeover contacts Wide vol..

Brand: SIEMENS | Manufacturer Part Number: 3RQ2000-2CW01



Manufacturer	SIEMENS
MPN / Reference	3RQ2000-2CW01
Catalog number	10000
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-44A6D5C853
Generated	2026-08-04

Product Overview

Coupling relay in industrial enclosure 3 hard gold-plated changeover contacts Wide voltage range 24 V to 240 V AC/DC
Spring-type terminals

INTERFACE (relay coupling) IM INDUSTRIAL BOX 3 COMMUTER. HARD GOLD VOLTAGE WIDE RANGE 24V AC/DC
UP TO 240V SPRING TERMINALS.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Function relays

Additional Product Information

Technical data

Coupling relay in industrial enclosure 3 hard gold-plated changeover contacts Wide voltage range 24 V to 240 V AC/DC
Spring-type terminals

product brand name SIRIUS

product designation Coupling relay in industrial enclosure

product type designation 3RQ2

General technical data

consumed active power 5 W

insulation voltage for overvoltage category III according to IEC 60664 with degree of pollution 3 rated value 300 V

degree of pollution 3

surge voltage resistance rated value 4 kV

maximum permissible voltage for safe isolation

? between auxiliary and auxiliary circuit 300 V
? between control and auxiliary circuit according to IEC 60947-1 300 V
protection class IP IP20
shock resistance
? according to IEC 60068-2-27 11g / 15 ms
? for railway applications according to EN 61373 Category 1, Class B
vibration resistance
? according to IEC 60068-2-6 10 ... 55 Hz: 0.35 mm
? for railway applications according to EN 61373 Category 1, Class B
switching behavior monostable
mechanical service life (switching cycles) typical 10 000 000
electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000
thermal current of the switching element with contacts maximum 5 A
reference code according to IEC 81346-2 K
Substance Prohibitance (Date) 05/31/2018
Control circuit/ Control
control supply voltage 1 at AC
? at 50 Hz 24 ... 240 V
? at 60 Hz 24 ... 240 V
control supply voltage 1
? at DC 24 ... 240 V
operating range factor control supply voltage rated value at DC
? initial v...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RQ2000-2CW01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.