

INDUSTRIAL COMPONENT DATA

3RS1020-2DW20 SIEMENS temperature monitoring relay Pt100, overshoot 2 threshold values, width 22.5 mm 0 °C t..

Brand: SIEMENS | Manufacturer Part Number: 3RS1020-2DW20



Manufacturer	SIEMENS
MPN / Reference	3RS1020-2DW20
Catalog number	10202
Category	Temperature monitoring relay
Minimum order	1 Pcs
Document ID	EO-BCEA1AD1D3
Generated	2026-08-06

Product Overview

temperature monitoring relay Pt100, overshoot 2 threshold values, width 22.5 mm 0 °C to 200 °C 24 - 240 V AC/DC 1 NO + 1 CO, Load and quiescent current spring-loaded terminal !!!phased-out product!!! the preferred successor is 3RS2600-2BW30

SIRIUS Temperature Monitoring Relay for PT100, excess exceed 2 thresholds, width 22.5 mm 0~C-200~C, 110-120/220-240V AC 1 NA+1 CNM, NA circuit and NC spring connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Function relays
--------------	--

Additional Product Information

Technical data

temperature monitoring relay Pt100, overshoot 2 threshold values, width 22.5 mm 0 °C to 200 °C 24 - 240 V AC/DC 1 NO + 1 CO, Load and quiescent current spring-loaded terminal !!!phased-out product!!! the preferred successor is 3RS2600-2BW30

product brand name SIRIUS

product designation Temperature monitoring relay

design of the product Overshoot, 2 threshold values

product type designation 3RS10

General technical data

power loss [W] maximum 2 W

power loss [V•A] maximum 4 VA
reference code according to IEC 81346-2 K
measurable temperature
? initial value 0 °C
? full-scale value 200 °C
Substance Prohibitance (Date) 05/01/2012
product function
? error memory No
? external reset No
design of the sensor connectable PT100 (resistance sensor)
Control circuit/ Control
type of voltage AC/DC
control supply voltage 1 at AC
? at 50 Hz 24 ... 240 V
? at 60 Hz 24 ... 240 V
control supply voltage 1
? at DC 24 ... 240 V
supply voltage frequency for auxiliary and control circuit 50 ... 60 Hz
number of measuring circuits 1
Auxiliary circuit
number of NC contacts for auxiliary contacts 0
number of NO contacts for auxiliary contacts 1
number of CO contacts for auxiliary contacts 1
Connections/ Terminals
type of electrical connection for auxiliary and control circuit spring-loaded terminals
type of electrical connection plug-in socket Yes
Installation/ mounting/ dimensions
fastening method screw and snap-on mounting onto 35 mm standard mounting rail
height 103 mm
width 22.5 mm
dep...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RS1020-2DW20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.