

INDUSTRIAL COMPONENT DATA

3RS1100-1CK20 SIEMENS temperature monitoring relay thermocouple type J, overshoot 1 threshold value, width 2..

Brand: SIEMENS | Manufacturer Part Number: 3RS1100-1CK20



Manufacturer	SIEMENS
MPN / Reference	3RS1100-1CK20
Catalog number	11001
Category	Temperature monitoring relay
Minimum order	1 Pcs
Document ID	EO-FE3BED3EB4
Generated	2026-08-06

Product Overview

temperature monitoring relay thermocouple type J, overshoot 1 threshold value, width 22.5 mm 0 °C to 200 °C
110-120/220-240 V AC 1 NO + 1 NC, quiescent current principle screw terminal !!!phased-out product!!! the preferred successor is 3RS2500-1AW30
SIRIUS Temperature monitoring relay thermocouple type J, excess 1 threshold, width 22.5 mm 0~C-200~C,
110-120/220-240V AC 1 NA + 1 NC, NC circuit screw connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Function relays

Additional Product Information

Technical data

temperature monitoring relay thermocouple type J, overshoot 1 threshold value, width 22.5 mm 0 °C to 200 °C
110-120/220-240 V AC 1 NO + 1 NC, quiescent current principle screw terminal !!!phased-out product!!! the preferred successor is 3RS2500-1AW30

product brand name SIRIUS

product designation Temperature monitoring relay

design of the product Overshoot, 1 threshold value

product type designation 3RS11

General technical data

reference code according to IEC 81346-2 K

measurable temperature

? initial value 0 °C

? full-scale value 200 °C

Substance Prohibitance (Date) 05/01/2012

product function

? error memory No

? external reset No

design of the sensor connectable type J (thermocouple)

Control circuit/ Control

type of voltage AC

control supply voltage 1 at AC

? at 50 Hz rated value 110 V

? at 60 Hz rated value 110 V

control supply voltage 2 at AC

? at 50 Hz rated value 230 V

? at 60 Hz rated value 230 V

supply voltage frequency for auxiliary and control circuit 50 ... 60 Hz

number of measuring circuits 1

Auxiliary circuit

number of NC contacts for auxiliary contacts 1

number of NO contacts for auxiliary contacts 1

number of CO contacts for auxiliary contacts 0

Connections/ Terminals

type of electrical connection for auxiliary and control circuit screw-type terminals

type of electrical connection plug-in socket Yes

Installation/ mounting/ dimensions

fastening method screw and snap-on mounting onto 35 mm standard mounting rail

height 102 mm

width 22.5 mm

depth 91...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RS1100-1CK20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.