

INDUSTRIAL COMPONENT DATA

3RS1140-2GW60 SIEMENS temperature monitoring relay

Thermocouple J, T, E, K, N 2 threshold values digitally a..

Brand: SIEMENS | Manufacturer Part Number: 3RS1140-2GW60



Manufacturer	SIEMENS
MPN / Reference	3RS1140-2GW60
Catalog number	11402
Category	Temperature monitoring relay
Minimum order	1 Pcs
Document ID	EO-4383AED56D
Generated	2026-08-06

Product Overview

temperature monitoring relay Thermocouple J, T, E, K, N 2 threshold values digitally adjustable -99 °C to 999 °C 24 - 240 V AC/DC 2 x 1 CO + 1 NO, width 45 mm spring-loaded terminal !!!phased-out product!!! the preferred successor is 3RS2600-1BW30

SIRIUS Temperature monitoring relay thermocouple J, T, E, K, N 2 thresholds, digital -99~C - 999~C, 24-240V AC/DC 2 X 1 CNM + 1 NA, width 45 mm spring connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Function relays

Additional Product Information

Technical data

temperature monitoring relay Thermocouple J, T, E, K, N 2 threshold values digitally adjustable -99 °C to 999 °C 24 - 240 V AC/DC 2 x 1 CO + 1 NO, width 45 mm spring-loaded terminal !!!phased-out product!!! the preferred successor is 3RS2600-1BW30

product brand name SIRIUS

product designation Temperature monitoring relay

design of the product 2 threshold values, digitally adjustable

product type designation 3RS11

General technical data

reference code according to IEC 81346-2 K

measurable temperature

? initial value -99 °C
? full-scale value 999 °C
Substance Prohibitance (Date) 05/01/2012
product function
? error memory Yes
? external reset Yes
design of the sensor connectable type J, K, T, E, N (thermocouple)
Control circuit/ Control
type of voltage AC/DC
control supply voltage 1 at AC
? at 50 Hz 24 ... 240 V
? at 60 Hz 24 ... 240 V
control supply voltage 1
? at DC 24 ... 240 V
supply voltage frequency for auxiliary and control circuit 50 ... 60 Hz
number of measuring circuits 1
Auxiliary circuit
number of NC contacts for auxiliary contacts 0
number of NO contacts for auxiliary contacts 1
number of CO contacts for auxiliary contacts 2
Connections/ Terminals
type of electrical connection for auxiliary and control circuit spring-loaded terminals
type of electrical connection plug-in socket Yes
Installation/ mounting/ dimensions
fastening method screw and snap-on mounting onto 35 mm standard mounting rail
height 108 mm
width 45 mm
depth 91 mm
Ambient conditions
a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RS1140-2GW60 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.