

INDUSTRIAL COMPONENT DATA

3RS1440-2HB50 SIEMENS Temperature monitoring relay for IO-Link PT100/1000, KTY83/84, NTC 2 limit values -50 ..

Brand: SIEMENS | Manufacturer Part Number: 3RS1440-2HB50



Manufacturer	SIEMENS
MPN / Reference	3RS1440-2HB50
Catalog number	14402
Category	Temperature monitoring relay
Minimum order	1 Pcs
Document ID	EO-79B8B346F9
Generated	2026-08-06

Product Overview

temperature monitoring relay for IO-Link Pt100/1000 KTY83/84, NTC 2 limit values -50 °C to 750 °C 3 x 1 CO, width 45 mm spring-loaded terminal !!!phased-out product!!! the preferred successor is 3RS2800-2BA40

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Function relays
--------------	--

Additional Product Information

Technical data

temperature monitoring relay for IO-Link Pt100/1000 KTY83/84, NTC 2 limit values -50 °C to 750 °C 3 x 1 CO, width 45 mm spring-loaded terminal !!!phased-out product!!! the preferred successor is 3RS2800-2BA40

product brand name SIRIUS

product designation Temperature monitoring relay

design of the product 2 threshold values, digitally adjustable

product type designation 3RS14

General technical data

power loss [W] maximum 4 W

power loss [V•A] maximum 7 VA

reference code according to IEC 81346-2 K

measurable temperature

? initial value -50 °C

? full-scale value 750 °C

Substance Prohibitance (Date) 05/01/2012

product function

? error memory Yes

? external reset Yes

design of the sensor connectable PT100/1000, KTY83/84, NTC (resistance sensors)

measurable temperature with KTY-sensor maximum 200 °C

sensor current with KTY-sensor 0.3 mA

Control circuit/ Control

type of voltage DC

control supply voltage 1

? at DC rated value 24 V

? at DC 18 ... 30 V

number of measuring circuits 1

Communication/ Protocol

protocol is supported IO-Link protocol Yes

IO-Link transfer rate COM2 (38,4 kBaud)

point-to-point cycle time between master and IO-Link device minimum 10 ms

type of voltage supply via input/output link master Yes

data volume

? of the address range of the inputs with cyclical transfer total 4 byte

? of the address range of the outputs with cyclical transfer total 2 byte

Auxiliary circuit

number of NC contacts for auxiliary contacts 0

number of NO contacts for auxiliary....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RS1440-2HB50 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.