

INDUSTRIAL COMPONENT DATA

3RS2140-1GD60 SIEMENS temperature monitoring relay

Thermocouple J, T, E, K, N 2 threshold values digitally a..

Brand: SIEMENS | Manufacturer Part Number: 3RS2140-1GD60



Manufacturer	SIEMENS
MPN / Reference	3RS2140-1GD60
Catalog number	21401
Category	Temperature monitoring relay
Minimum order	1 Pcs
Document ID	EO-3814DC7F55
Generated	2026-08-06

Product Overview

temperature monitoring relay Thermocouple J, T, E, K, N 2 threshold values digitally adjustable -99 °F to 1830 °F 24 V AC/DC 2 x 1 CO + 1 NO, width 45 mm screw terminal !!!phased-out product!!! the preferred successor is 3RS2600-1BA30 TEMPERATURE MONITORING RELAY THERMOCOUPLE J, T, E, K, N 2 THRESHOLDS, DIGITAL -99 DEGREES F TO 1830 DEGREES F 24 V AC/DC 2 X 1 C + 1NA, WIDTH 45 MM SCREW CONNECTION. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Function relays

Additional Product Information

Technical data

temperature monitoring relay Thermocouple J, T, E, K, N 2 threshold values digitally adjustable -99 °F to 1830 °F 24 V AC/DC 2 x 1 CO + 1 NO, width 45 mm screw terminal !!!phased-out product!!! the preferred successor is 3RS2600-1BA30 product brand name SIRIUS

product designation Temperature monitoring relay

product type designation 3RS21

General technical data

product function temperature monitoring

reference code according to IEC 81346-2 K

measurable Fahrenheit temperature

? initial value -99 °F

? full-scale value 1 830 °F

Substance Prohibitance (Date) 05/01/2012

product function

? error memory Yes

? external reset Yes

design of the sensor connectable type J, K, T, E, N (thermocouple)

Control circuit/ Control

control supply voltage 1 at AC

? at 50 Hz rated value 24 V

? at 60 Hz rated value 24 V

control supply voltage 1

? at DC rated value 24 V

supply voltage frequency for auxiliary and control circuit 50 ... 60 Hz

number of measuring circuits 1

Auxiliary circuit

number of NC contacts for auxiliary contacts 0

number of NO contacts for auxiliary contacts 1

number of CO contacts for auxiliary contacts 2

Connections/ Terminals

type of electrical connection

? for auxiliary and control circuit screw-type terminals

type of electrical connection plug-in socket Yes

Installation/ mounting/ dimensions

fastening method screw and snap-on mounting onto 35 mm standard mounting rail

height 106 mm

width 45 mm

depth 91 mm

Ambient conditions

ambient temperature

? during operat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RS2140-1GD60 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.