

## INDUSTRIAL COMPONENT DATA

**3RT1034-3AL20-1AA0 SIEMENS Power contactor, AC-3 32 A, 15 kW / 400 V 230 V AC, 50 / 60 Hz, 3-pole, Size S2 M..**

Brand: SIEMENS | Manufacturer Part Number: 3RT1034-3AL20-1AA0



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 3RT1034-3AL20-1AA0            |
| Catalog number  | 10000                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-40E6F2A3C6                 |
| Generated       | 2026-08-05                    |

**Product Overview**

Power contactor, AC-3 32 A, 15 kW / 400 V 230 V AC, 50 / 60 Hz, 3-pole, Size S2 Main circuit: screw terminal, Auxiliary circuit: Spring-type terminal Upright mounting position !!! Phased-out product !!! Successor is SIRIUS 3RT2 Preferred successor type is >>3RT2035-3AL20-1AA0

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |         |
|--------------|---------|
| Catalog path | SIEMENS |
|--------------|---------|

**Additional Product Information**

ETIM: EC000066 - Power contactor, AC switching

Value Unit

Rated control supply voltage  $U_s$  at DC (EF003980) - V

Rated operation power NEMA (EF011960) - kW

Rated control supply voltage  $U_s$  at AC 50HZ (EF003978) ['230', '230'] V

Rated control supply voltage  $U_s$  at AC 60HZ (EF003979) ['230', '230'] V

Voltage type for actuating (EF008242) AC

Rated operation current  $I_e$  at AC-1, 400 V (EF001393) 50 A

Rated operation current  $I_e$  at AC-3, 400 V (EF001392) 32 A

Rated operation power at AC-3, 400 V (EF001364) 15.0 kW

Rated operation current  $I_e$  at AC-4, 400 V (EF008495) 29 A

Rated operation power at AC-4, 400 V (EF008496) 15.0 kW

Modular version (EF001126) true

Number of auxiliary contacts as normally open contact (EF001376) 0

Number of auxiliary contacts as normally closed contact (EF001377) 0

Type of electrical connection of main circuit (EF006819) Screw connection

Number of normally closed contacts as main contact (EF001375) 0

Number of main contacts as normally open contact (EF001374) 3

Power contactor, AC-3 32 A, 15 kW / 400 V 230 V AC, 50 / 60 Hz, 3-pole, Size S2 Main circuit: screw terminal, Auxiliary circuit: Spring-type terminal Upright mounting position !!! Phased-out product !!! Successor is SIRIUS 3RT2 Preferred successor type is >>3RT2035-3AL20-1AA0

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT1034-3AL20-1AA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.