

## INDUSTRIAL COMPONENT DATA

**3RT1036-3BB44-3MA0 SIEMENS Power contactor, AC-3 50 A, 22 kW / 400 V 24 V DC, 3-pole, Size S2, spring-type t..**

Brand: SIEMENS | Manufacturer Part Number: 3RT1036-3BB44-3MA0



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 3RT1036-3BB44-3MA0            |
| Catalog number  | 10363                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-26959D1C52                 |
| Generated       | 2026-08-05                    |

**Product Overview**

Power contactor, AC-3 50 A, 22 kW / 400 V 24 V DC, 3-pole, Size S2, spring-type terminal 2 NO + 2 NC, captive !!!  
Phased-out product !!! Successor is SIRIUS 3RT2 Preferred successor type is >>3RT2036-3KB44-3MA0

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

**Additional Product Information**

ETIM: EC000066 - Power contactor, AC switching

Value Unit

Rated operation power NEMA (EF011960) - kW

Rated control supply voltage  $U_s$  at DC (EF003980) ['-', '24'] V

Voltage type for actuating (EF008242) DC

Rated operation current  $I_e$  at AC-1, 400 V (EF001393) 60 A

Rated operation current  $I_e$  at AC-3, 400 V (EF001392) 50 A

Rated operation power at AC-3, 400 V (EF001364) 22.0 kW

Rated operation current  $I_e$  at AC-4, 400 V (EF008495) 41 A

Rated operation power at AC-4, 400 V (EF008496) 22.0 kW

Modular version (EF001126) true

Number of auxiliary contacts as normally open contact (EF001376) 2

Number of auxiliary contacts as normally closed contact (EF001377) 2

Type of electrical connection of main circuit (EF006819) Screw connection

Number of normally closed contacts as main contact (EF001375) 0

Number of main contacts as normally open contact (EF001374) 3

Rated control supply voltage Us at AC 50HZ (EF003978) - V

Rated control supply voltage Us at AC 60HZ (EF003979) - V

Power contactor, AC-3 50 A, 22 kW / 400 V 24 V DC, 3-pole, Size S2, spring-type terminal 2 NO + 2 NC, captive !!!

Phased-out product !!! Successor is SIRIUS 3RT2 Preferred successor type is >>3RT2036-3KB44-3MA0

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT1036-3BB44-3MA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.