

INDUSTRIAL COMPONENT DATA

3RT1044-1BE44 SIEMENS Power contactor, AC-3 65 A, 30 kW / 400 V 60 V DC, 2 NO + 2 NC, 3-pole, Size S3, Screw..

Brand: SIEMENS | Manufacturer Part Number: 3RT1044-1BE44



Manufacturer	SIEMENS
MPN / Reference	3RT1044-1BE44
Catalog number	10441
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-590DD9860E
Generated	2026-08-06

Product Overview

Power contactor, AC-3 65 A, 30 kW / 400 V 60 V DC, 2 NO + 2 NC, 3-pole, Size S3, Screw terminal !!! Phased-out product
!!! Successor is SIRIUS 3RT2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors

Additional Product Information

ETIM: EC000066 - Power contactor, AC switching

Value Unit

Rated control supply voltage U_s at AC 50HZ (EF003978) - V

Rated operation power NEMA (EF011960) - kW

Rated control supply voltage U_s at AC 60HZ (EF003979) - V

Rated control supply voltage U_s at DC (EF003980) ['60', '60'] V

Voltage type for actuating (EF008242) DC

Rated operation current I_e at AC-1, 400 V (EF001393) 100 A

Rated operation current I_e at AC-3, 400 V (EF001392) 65 A

Rated operation power at AC-3, 400 V (EF001364) 30.0 kW

Rated operation current I_e at AC-4, 400 V (EF008495) 55 A

Rated operation power at AC-4, 400 V (EF008496) 30.0 kW

Modular version (EF001126) true

Number of auxiliary contacts as normally open contact (EF001376) 2

Number of auxiliary contacts as normally closed contact (EF001377) 2

Type of electrical connection of main circuit (EF006819) Screw connection

Number of normally closed contacts as main contact (EF001375) 0

Number of main contacts as normally open contact (EF001374) 3

Power contactor, AC-3 65 A, 30 kW / 400 V 60 V DC, 2 NO + 2 NC, 3-pole, Size S3, Screw terminal !!! Phased-out product

!!! Successor is SIRIUS 3RT2

product brand name SIRIUS

Product designation power contactor

General technical data

Size of contactor S3

? Insulation voltage rated value 1 000 V

Degree of pollution 3

Surge voltage resistance rated value 6 kV

maximum permissible voltage for safe isolation

? between coil and main contacts acc. to EN 60947-1 690 V

? protection class IP on the front IP20; IP20 on the front...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT1044-1BE44 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.