

**INDUSTRIAL COMPONENT DATA**

# 3RT1075-2AF36 SIEMENS power contactor, AC-3 400 A, 200 kW / 400 V AC (50-60 Hz) / DC operation 110-127 V AC/..

Brand: SIEMENS | Manufacturer Part Number: 3RT1075-2AF36



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 3RT1075-2AF36                 |
| Catalog number  | 10752                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-CB779F85CD                 |
| Generated       | 2026-08-05                    |

## Product Overview

power contactor, AC-3 400 A, 200 kW / 400 V AC (50-60 Hz) / DC operation 110-127 V AC/DC auxiliary contacts 2 NO + 2 NC 3-pole, frame size S12 busbar connections drive: conventional spring-loaded terminal  
SIRIUS Contactor, 200KW/400V/AC-3 drive AC/DC 110-127V UC Auxiliary contacts 2NA+2NC 3 poles, size S12 terminals  
for control bar connection: conventional Spring connection. Manufactured to order. Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

## Additional Product Information

**Technical data**

power contactor, AC-3 400 A, 200 kW / 400 V AC (50-60 Hz) / DC operation 110-127 V AC/DC auxiliary contacts 2 NO + 2 NC 3-pole, frame size S12 busbar connections drive: conventional spring-loaded terminal

product brand name SIRIUS

product designation Power contactor

product type designation 3RT1

**General technical data**

size of contactor S12

product extension

? function module for communication No

? auxiliary switch Yes

power loss [W] for rated value of the current

? at AC in hot operating state 105 W  
? at AC in hot operating state per pole 35 W  
? without load current share typical 10 W  
insulation voltage  
? of main circuit with degree of pollution 3 rated value 1 000 V  
? of auxiliary circuit with degree of pollution 3 rated value 500 V  
surge voltage resistance  
? of main circuit rated value 8 kV  
? of auxiliary circuit rated value 6 kV  
maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1 690 V  
shock resistance at rectangular impulse  
? at AC 8,5g / 5 ms, 4,2g / 10 ms  
? at DC 8,5g / 5 ms, 4,2g / 10 ms  
shock resistance with sine pulse  
? at AC 13,4g / 5 ms, 6,5g / 10 ms  
? at DC 13,4g / 5 ms, 6,5g / 10 ms  
mechanical service life (switching cycles)  
? of contactor typical 10 000 000  
? of the contactor with added electronically optimized auxiliary switch block typical 5 000 000  
? of the contactor with added auxiliary switch block typical 10 000 000  
reference code according to IEC 81346-2 Q  
Substance Prohibitance (Date) 05/0...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT1075-2AF36 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.