

INDUSTRIAL COMPONENT DATA

3RT1535-1AH20 SIEMENS Power contactor, AC-3 40 A, 18.5 kW / 400 V 48 V AC, 50/60 Hz 4-pole, 2 NO + 2 NC, Siz..

Brand: SIEMENS | Manufacturer Part Number: 3RT1535-1AH20



Manufacturer	SIEMENS
MPN / Reference	3RT1535-1AH20
Catalog number	15351
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-A21B572325
Generated	2026-08-05

Product Overview

Power contactor, AC-3 40 A, 18.5 kW / 400 V 48 V AC, 50/60 Hz 4-pole, 2 NO + 2 NC, Size S2 Screw terminal !!!

Phased-out product !!! Successor is SIRIUS 3RT2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

ETIM: EC000066 - Power contactor, AC switching

Value Unit

Rated operation power NEMA (EF011960) - kW

Rated control supply voltage U_s at DC (EF003980) ['-', '-'] V

Voltage type for actuating (EF008242) AC

Rated operation current I_e at AC-1, 400 V (EF001393) 60 A

Rated operation current I_e at AC-3, 400 V (EF001392) 40 A

Rated operation power at AC-3, 400 V (EF001364) 18.5 kW

Rated operation current I_e at AC-4, 400 V (EF008495) - A

Rated operation power at AC-4, 400 V (EF008496) - kW

Modular version (EF001126) true

Number of auxiliary contacts as normally open contact (EF001376) 0

Number of auxiliary contacts as normally closed contact (EF001377) 0

Type of electrical connection of main circuit (EF006819) Screw connection

Number of normally closed contacts as main contact (EF001375) 2
Number of main contacts as normally open contact (EF001374) 2
Rated control supply voltage Us at AC 50HZ (EF003978) - V
Rated control supply voltage Us at AC 60HZ (EF003979) - V
Power contactor, AC-3 40 A, 18.5 kW / 400 V 48 V AC, 50/60 Hz 4-pole, 2 NO + 2 NC, Size S2 Screw terminal !!!
Phased-out product !!! Successor is SIRIUS 3RT2
product brand name SIRIUS
Product designation power contactor
General technical data
Size of contactor S2
? Insulation voltage of main circuit with degree of pollution 3 rated value 690 V
? Insulation voltage of auxiliary circuit with degree of pollution 3 rated value 690 V
Surge voltage resistance
? of main circuit rated value 6 kV
? of auxiliary circuit rated value 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT1535-1AH20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.