

INDUSTRIAL COMPONENT DATA

3RT2015-1SB42 SIEMENS Power contactor, AC-3 7 A, 3 kW / 400 V 1 NC, 24 V DC, 0.85-1.85*US with integrated su..

Brand: SIEMENS | Manufacturer Part Number: 3RT2015-1SB42



Manufacturer	SIEMENS
MPN / Reference	3RT2015-1SB42
Catalog number	20151
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-0B60F71D9D
Generated	2026-08-05

Product Overview

Power contactor, AC-3 7 A, 3 kW / 400 V 1 NC, 24 V DC, 0.85-1.85*US with integrated suppressor diode Size S00, screw terminal

SIRIUS Innovations Contactor coupling, AC-3, 3KW/400V, 1NC, DC 24V, 0, 85...1, 85*US, with diode, S00, screw connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Power contactor, AC-3 7 A, 3 kW / 400 V 1 NC, 24 V DC, 0.85-1.85*US with integrated suppressor diode Size S00, screw terminal

product brand name SIRIUS

product designation Coupling contactor

product type designation 3RT2

General technical data

size of contactor S00

product extension

? function module for communication No

? auxiliary switch No

power loss [W] for rated value of the current

? at AC in hot operating state 1.2 W
? at AC in hot operating state per pole 0.4 W
? without load current share typical 1.6 W
insulation voltage
? of main circuit with degree of pollution 3 rated value 690 V
? of auxiliary circuit with degree of pollution 3 rated value 690 V
surge voltage resistance
? of main circuit rated value 6 kV
? of auxiliary circuit rated value 6 kV
maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1 400 V
shock resistance at rectangular impulse
? at DC 6,7g / 5 ms, 4,2g / 10 ms
shock resistance with sine pulse
? at DC 10,5g / 5 ms, 6,6g / 10 ms
mechanical service life (switching cycles)
? of contactor typical 30 000 000
? of the contactor with added electronically optimized auxiliary switch block typical 5 000 000
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -55 ... +80 °C
relative humidity minimum 10 %
relative hu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT2015-1SB42 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.